

Product Brochure For S609

Mechanical Guillotine - MG-432

1250 x 3mm Mild Steel Shearing Capacity

Manual Backgauge



| | |
|--|--------|
| ORDER CODE: | S609 |
| MODEL: | MG-432 |
| Shearing Capacity - Mild Steel (mm): | 3 |
| Shearing Capacity - Stainless Steel (mm): | ~ |
| Shearing Length (mm): | 1250 |
| NC Control (Type): | ~ |
| Backgauge (Type): | Manual |
| Backgauge Travel (mm): | 635 |
| Pneumatic Sheet Supports: | ~ |
| Quick Action Blade Clearance Adjustment: | ~ |
| Strokes / min (SPM): | 33 |
| Blade Angle (deg): | 2.1° |
| Throat Depth (mm): | ~ |
| Motor Power (kW / hp): | 3 / 4 |
| Voltage / Amperage (V / amp): | 415 |
| Floor Space Requirements (L x W x H) (mm): | ~ |
| Nett Weight (kg): | 1140 |



Features


- Mechanical operation for high stroke rate
- 1250mm x 3mm cutting capacity
- Single or multiple cutting
- Blades made from 9CrSi material with two cutting edges
- Material squaring edge
- Front sheet supports
- Foot pedal control
- 3kW 415V motor
- 635mm wind-out Backgauge with mechanical counter
- Rear guarding included
- Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
 1. Guillotine is run & tested prior delivery

Product Brochure For S609

Specific Features



Right View



Side View




Rear View



Hinged Rear Gate with Gas Strut Support



Safety Micro Switch on Rear Gate



Backgauge Handwheel with Digit Counter



Material Viewing Windows



Industrial Roving Foot Pedal



Emergency Stop and Cut Counter



Switches



Main Isolation Switch



Shown with Optional Ball Transfer Tables - Order Code (L840)