

Product Brochure For P136P

## AP-1020/100 - Industrial Hydraulic Press Bender

100 Tonne  
 Includes Pressbrake Attachment

**On Sale**

Ex GST	Inc GST
<b>\$14,500.00</b>	<b>\$15,950.00</b>
<b>\$13,590.00</b>	<b>\$14,949.00</b>



ORDER CODE:	P136P
MODEL:	AP-1020/100 - Pressbrake
Pressing Capacity (Tonne):	100
Hydraulic Ram Operation (Type):	Motorised / Hydraulic
Sliding Ram (left-right) (Yes / No):	No
Width Between Front Posts (mm):	1020
Width Between Side Posts (mm):	~
Table Top Opening - (Front to Back) (mm):	~
Ram To Table (Max.) (mm):	~
Piston Ram Stroke (mm):	300
Ram Diameter (mm):	Ø220
Cylinder Piston Bore Diameter (mm):	~
Motor Power (kW / hp):	7.5 / 10
Voltage (V):	415
Floor Space (W x D x H) (mm):	2100 x 1050 x 2220
Shipping Dimensions (L x W x H) (mm):	2100 x 1050 x 2220
Nett Weight (kg):	1900

LFSS  
 ŞAHİN MAKİNA



### Description

100 tonne Hydraulic Press Bender Includes a Pressbrake Attachment

Note: Pressbrake attachment can be removed to use as a standard shop press

### Features

- Top gooseneck pressbrake die and holders
- Bottom multi-vee die 8, 20, 32, 40 & 65mm
- 8mm maximum plate bending thickness with pressbrake attachment
- 680mm distance between tables
- 1020 x 500mm die table with a Ø100mm centre hole
- Fast approach slow bend
- Adjustment system for taking down or up the table
- Pressure adjustment
- Adjustable stroke
- T-slotted bottom table
- High capacity workshop forming press with extra 2 guide pistons in both sides
- Heavy duty steel welded frame
- Hydraulic operated pressing ram
- Pressure gauge fitted
- Safety overload valve
- Built to CE regulations
- Foot Pedal control
- Safety contactor switch with overload protection
- 8mm/sec Fast Approach
- 5mm/sec Working Speed
- 10mm/sec Return Speed

- Pre-Commissioning:
  1. Press is run & tested prior delivery
  2. Hydraulic oil is included with machine

### Includes

Complete with Pressbrake Attachment

•  
**Specific Features**



Bending Sheet Metal

**Recommended Accessories**

O002

Superdraulic Hi Temp 46  
Hydraulic Oil



O004

Superdraulic 46 Hydraulic Oil

