

Product Brochure For S772

AR-2506 - Motorised Plate Curving Rolls

2550 x 6mm Mild Steel Capacity
 Initial Pinch Design

Ex GST	Inc GST
\$15,650.00	\$17,215.00
\$15,150.00	\$16,665.00
Special Ends 25/11/2018	

ORDER CODE:	S772
MODEL:	AR-2506
Curving System Type:	Initial Pinch
Curving Material Length (mm):	2550
Curving Plate Thickness - Mild Steel (mm):	6
Minimum Rolling Diameter (mm):	400
Roll Diameter (mm):	190
Motor Power (kW / hp):	5.5 / 7.5
Voltage / Amperage (V / amp):	415
Dimensions (LxWxH) (mm):	4160 x 900 x 1200
Shipping Dimensions (L x W x H) (cm):	416 x 90 x 120
Nett Weight (kg):	3200



Features

- Two rolls powered by gearbox and gear system
- Drive motor fitted with brake preventing material roll on
- Swing out end enables complete cylinder to be removed
- Heavy duty steel welded main frames
- Mobile control panel
- Safety wire interlock system with emergency shut-off
- Motorised up & down rear curving roll
- Mild steel capacity is rated on hot rolled material with 250MPA

Product Brochure For S772

Specific Features



Left View



Right View




Rear View




Roving Pendant Control




Control Panel




Right End View



Swing Out Top Roller



Side View



Motorised Up/Down Rear Curving Roll




Safety Wire Interlock System



Initial Pinch Roller Design



End View



Main Power Isolation Switch



Shown with Optional Ball Transfer Tables

Recommended Accessories

L840

Ball Transfer Table - Sheet
Metal & Plate

