

Product Brochure For B006

Metal Cutting Band Saw - Swivel Vice - BS-7L

Mitre Cuts Up To 45° & Includes Hydraulic Downfeed Control
 305 x 178mm (W x H) Rectangle Capacity



ORDER CODE:	B006
MODEL:	~
Swing Over Bed (mm):	~
Distance Between Centres (mm):	~
Spindle Bore (mm):	~
Swing In Gap (mm):	~
Swing Over Cross-slide (mm):	~
Digital Readout System Fitted:	~
Quick Change Toolpost Fitted:	~
Leadscrew Covers Fitted:	~
Taper Turning Attachment:	~
Coolant System:	~
Tool Height To Suit (mm):	~
Centre Height (mm):	~
Spindle Nose Size or Type:	~
Bed Width (mm):	~
Headstock Spindle Taper (MT):	~
Tailstock Taper (MT):	~
Cross Slide Travel (mm):	~
Compound Slide Travel (mm):	~
Leadscrew Type:	~
Metric Cross Feed (X-Axis) (mm/rev):	~
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	~
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	~
Imperial Thread Steps & TPI (No. / TPI):	~
3 Jaw Chuck Diameter (mm):	~
4 Jaw Chuck Diameter (mm):	~
Spindle Steps / Speeds (No. / rpm):	~
Motor Power (kW / hp):	~
Voltage / Amperage (V / amp):	~
Nett Weight (kg):	~

Description

Looking for a 7" metal bandsaw that outshines the competition in quality and reliability? Our Metalmaster BS-7L is the perfect solution. While our competitors may offer similar-looking products at a lower price, our bandsaw's superior craftsmanship and our company's 90-year legacy in the industry set us apart. We have been delivering unmatched quality and durability for decades, ensuring that you invest in machinery that is built to last.

Features

- 305 x 178mm (W x H) rectangular capacity
- Adjustable hydraulic feed cutting rate for multiple applications
- Mitre cuts to 45° using calibrated vice
- Built-in coolant system for maximum cutting efficiency
- Limit switch stops machine when cut is complete
- Adjustable blade roller guides provides accurate cutting
- Adjustable 4-speed pulley drive system enabling 22-34-49-64mpm cutting speeds
- Adjustable length stop for repetition cutting
- Coolant system with flow control valve
- Wire wheel brush to clean swarf from blade
- Portable - on wheels for ease of use
- Vertical cutting table included
- Automatic electric cut-out switch
- Heavy-duty 0.75kW 1hp 240V fully enclosed fan-cooled motor

Product Brochure For B006

Specific Features



Left View



Head Fully Raised



Rear View



Rear Left View




Shown Set Up with Vertical Cutting Table



Shown Set Up with Vertical Cutting Table Rear View



Vertical Cutting Table




Hydraulic Ram Down Feed Control



Blade Guide



Down Feed Control



Speed Chart



Coolant System

Product Brochure For B006

Recommended Accessories

B210

Metal Band Saw Blade - 6TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B212

Metal Band Saw Blade - 8TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B214

Metal Band Saw Blade - 10TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B216

Metal Band Saw Blade - 14TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B400

Metal Band Saw Blade - 4-6TPI
 Bi-Metal, Blade - 2362 x 19 x
 0.80mm



B404

Metal Band Saw Blade -
 6-10TPI Bi-Metal, Blade - 2362 x
 19 x 0.80mm



B408

Metal Band Saw Blade -
 10-14TPI Bi-Metal, Blade - 2362
 x 19 x 0.80mm



S091

Soluble Metal Cutting Fluid - 20
 Litre



Product Brochure For B006

S090A

Soluble Metal Cutting Fluid - 1 Litre



S090

Soluble Metal Cutting Fluid - 5 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste - 200g



S074

Cutting Tool Lubricant Paste - 500g



L300

Magnetic Swarf Remover



M9991

Magnetic Floor Sweeper



L812

Roller Conveyor



L816

Roller Conveyor Stand



W343A

Roller Stand



M800


Rubber Mat - Anti-Fatigue



Product Brochure For B006

M805

Rubber Mat - Anti-Fatigue



O000

SpillFix Universal Organic Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive

