

Product Brochure For B008G

Swivel Head Band Saw - BS-7GRD

215 x 178mm (W x H) Rectangle Capacity



ORDER CODE:	B008G
MODEL:	BS-7GRD
Operation Type:	Swivel Head
Round @ 90° (mm):	178
Round @ 45° (mm):	127
Round @ 60° (mm):	~
Square @ 90° (mm):	178
Square @ 45° (mm):	85
Square @ 60° (mm):	~
Rectangle (W x H) @ 90° (mm):	215 x 178
Rectangle (W x H) @ 45° (mm):	140 x 85
Rectangle (W x H) @ 60° (mm):	~
Coolant System:	Yes
Table Working Height (mm):	850
Base Dimensions (mm):	~
Cutting Head Beam Type:	Manual
Cutting Head Beam Return:	Manual Return
Cutting Head Down Feed Control:	Adjustable Hydraulic
Vice Clamping Fixture:	Manual
Bundle Cutting Fixture:	~
Blade Steps / Speeds (M/Min):	34-50-65
Blade Size (L x W x T) (mm):	2362 x 19 x 0.8
Motor Power (kW / hp):	0.75 / 1
Voltage / Amperage (V / amp):	240
Nett Weight (kg):	165

Description

The BS-7GRD medium duty swivel head metal cutting band saw has many features on offer with a double mitre swivel head capable of cutting up to 178mm diameter or 215 x 178mm in steel at 90°. There is a choice of three blade speeds via an adjustable 3 stage geared drive system so that the cutting speed can be changed to suit a wide range of materials, whilst the built-in coolant system ensures maximum cutting efficiency and long blade life.

The cutting operation works automatically with the weight of the head providing the cutting force and a limit switch shutting the machine down when the cut is complete. The weight of the head is counterbalanced by an adjustable hydraulic damper to control the feed rate, an excellent machine choice for maintenance shops, medium steel fabrications, and engineering workshops.

Features

- 215 x 178mm (W x H) rectangular capacity
- ±45° swivel head for easy angle cutting without moving material
- Adjustable hydraulic feed cutting rate for multiple applications
- Dual mitre cutting capabilities to 45° via swivelling head and sliding vice
- Built-in coolant system for maximum cutting efficiency
- Limit switch stops machine when cut is complete
- Coolant system with flow control valve
- Quick action material clamping lever
- Adjustable blade roller guides provides accurate cutting
- 3-speed geared drive system enabling 34-50-65mpm cutting speeds
- Adjustable length stop for repetition cutting
- Wire wheel brush to clean swarf from blade
- Automatic electric cut-out switch
- Heavy-duty 750W/240V fully enclosed fan-cooled motor

Product Brochure For B008G

Specific Features



Geared Drive Motor



Speed Change Dial



Blade Guide



Coolant to Blades



Head Release Handle



Hydraulic Ram for Cutting Feed Rate



Swivel Head



Quick Action Vice Handle Lever



Rear View



Coolant System



Blade Loose and Tight Handle



Band Dynamometric Tension Indicator

Product Brochure For B008G

Recommended Accessories

B210

Metal Band Saw Blade - 6TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B212

Metal Band Saw Blade - 8TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B214

Metal Band Saw Blade - 10TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B216

Metal Band Saw Blade - 14TPI
 Carbon, Blade - 2362 x 19 x
 0.80mm



B400

Metal Band Saw Blade - 4-6TPI
 Bi-Metal, Blade - 2362 x 19 x
 0.80mm



B404

Metal Band Saw Blade -
 6-10TPI Bi-Metal, Blade - 2362 x
 19 x 0.80mm



B408

Metal Band Saw Blade -
 10-14TPI Bi-Metal, Blade - 2362
 x 19 x 0.80mm



S090A

Soluble Metal Cutting Fluid - 1
 Litre



Product Brochure For B008G

S090

Soluble Metal Cutting Fluid - 5 Litre



S091

Soluble Metal Cutting Fluid - 20 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste - 200g



W3434

Roller Stand



W3436

Roller Stand - V-Type



M970

Digital Angle Rule



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive



Product Brochure For B008G

O000

SpillFix Universal Organic Absorbent



L300

Magnetic Swarf Remover




M9991

Magnetic Floor Sweeper



M805

Rubber Mat - Anti-Fatigue



M800

Rubber Mat - Anti-Fatigue



L812

Roller Conveyor



L816

Roller Conveyor Stand



L802

3m Length Stop System



L803

Manual Stop With Arm



P232

Coolant Pump

