Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For B014

Metal Cutting Band Saw - Swivel Vice - BS-912

Mitre Cuts Up To 45º, Quick Action Material Clamp & Includes Hydraulic Downfeed Control

BS-912 - 305 x 178mm (W x H) Rectangle Capacity

On Sale

Ex GST	Inc GST
~~$2,180.00~~	~~$2,398.00~~
$2,050.00	$2,255.00



ORDER CODE:	B014
MODEL:	BS-912
Operation Type:	Fixed Head
Round @ 90º (mm):	230
Round @ 45º (mm):	150
Round @ 60º (mm):	~
Square @ 90º (mm):	230
Square @ 45º (mm):	127
Square @ 60º (mm):	~
Rectangle (W x H) @ 90º (mm):	305 x 178
Rectangle (W x H) @ 45º (mm):	150 x 127
Rectangle (W x H) @ 60º (mm):	~
Coolant System:	Yes
Table Working Height (mm):	640
Base Dimensions (mm):	~
Cutting Head Beam Type:	Manual
Cutting Head Beam Return:	Manual Return
Cutting Head Down Feed Control:	Adjustable Hydraulic
Vice Clamping Fixture:	Manual
Bundle Cutting Fixture:	~
Blade Steps / Speeds (M/Min):	26-50-73-96
Blade Size (L x W x T) (mm):	2654 x 27 x 0.9
Motor Power (kW / hp):	0.75 / 1
Voltage / Amperage (V / amp):	240 / 10
Nett Weight (kg):	185

Description

Manufactured in Taiwan

The BS-912 is a larger 240 volt band saw suitable for the medium fabrication and general engineering workshops. It features increased motor power, four blade speeds, double row ball bearing blade guides, a built-in coolant system and greatly increased cutting capacity.

The downward cutting pressure is controlled by a fully adjustable hydraulic damper with an on/off valve and there is an automatic cut-off at the end of the cut. The vice rotates for mitre cutting and there is an adjustable material stop for consistent repeat length cutting.


Features

- 305 x 178mm (W x H) rectangular capacity
- Adjustable hydraulic feed cutting rate for multiple applications
- Mitre cuts to 45º using calibrated vice
- Built-in coolant system to both blade guides for maximum cutting efficiency
- Limit switch stops machine when cut is complete
- Quick action material clamping lever
- Adjustable blade roller guides provides accurate cutting
- Adjustable 4-speed pulley drive system enabling 26-50-73-96mpm cutting speeds
- Adjustable length stop for repetition cutting
- Wire wheel brush to clean swarf from blade
- Portable - on wheels for ease of use
- Automatic electric cut-out switch
- Heavy-duty 750W 240V fully enclosed fan-cooled motor

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au


Product Brochure For B014


Specific Features


Bearing Blade Guide


Hydraulic Ram Down Feed Control


Hydraulic Ram


Length Stop



Speed Chart


Coolant System


Blade Guide Wire Brush


Bearing Blade Guide


Guide Adjustment

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For B014

Recommended Accessories

B412

Metal Band Saw Blade - 4-6TPI Bi-Metal, Blade - 2654 x 25.4 x 0.90mm



B414

Metal Band Saw Blade - 6-10TPI Bi-Metal, Blade - 2654 x 25.4 x 0.90mm



B418

Metal Band Saw Blade - 10-14TPI Bi-Metal, Blade - 2654 x 25.4 x 0.90mm



S090A

Soluble Metal Cutting Fluid - 1 Litre



S090

Soluble Metal Cutting Fluid - 5 Litre



W3434

Roller Stand



W3436

Roller Stand - V-Type



L300

Magnetic Swarf Remover



Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For B014

L812
Roller Conveyor



L816
Roller Conveyor Stand



L802
3m Length Stop System



L803
Manual Stop With Arm

