

## Product Brochure For B462

### Metal Band Saw Blade - 2-3TPI Bi-Metal, Blade - 3302 x 25.4 x 0.9mm

Suits Stainless Steel

SUITS BS-250 or BS-10L Metal Cutting Band Saws

Ex GST

\$95.00

Inc GST

\$104.50



|                                     |                        |
|-------------------------------------|------------------------|
| ORDER CODE:                         | B462                   |
| Suits Band Saw Models:              | BS-250 or BS-10L       |
| Blade Size (L x W x T) (mm):        | 3302 x 25.4 x 0.90     |
| Number of teeth per inch (TPI):     | 2-3                    |
| Blade Type:                         | BI-METAL               |
| Blade Suitable for - Material Type: | Mild & Stainless Steel |
| Suits Section Size (mm):            | 121-200                |



### Description

Please Note:

Starrett Blades are distributed in Sydney, Adelaide & Brisbane, Auckland & Christchurch  
 Excision Blades are distributed in Melbourne & Perth

#### IMPORTANT RUN-IN INSTRUCTIONS FOR BI-METAL BLADES

- Avoid excessive feed pressure on run-in
- Run-in at 3/4 normal feed pressure for first 25 square inches on tough material
- After run-in, gradually increase feed to maximum cutting rate

## Product Brochure For B462


### BLADE SELECTION CHARTS

Band saw tooth size is determined by the size of the cross section to be cut. In general cutting thinner sections requires more teeth per inch, thicker sections require coarser pitches, or less teeth per inch.

To select an appropriate tooth size please refer to the table immediately below unless material to be cut is a tube, in which case refer to the larger table below. For general purpose cutting use a constant pitch blade, for more aggressive production cutting of harder to cut materials use a variable pitch blade.

#### SOLID SECTION

| Section Size (mm) | Constant Pitch (TPI) | Variable Pitch (TPI) |
|-------------------|----------------------|----------------------|
| Up to 10          | 24 or 18             | 14/18 or 10/14       |
| 10-15             | 14                   | 8-12                 |
| 16-30             | 10                   | 6-10                 |
| 31-50             | 8                    | 5-8                  |
| 51-80             | 6                    | 4-6                  |
| 81-120            | 4                    | 3-4                  |
| 121-200           | 3                    | 2-3                  |
| Over 200          | 2 or 1.25            | 1.4-2 or 0.8-1.3     |



#### TUBE SECTION

| Wall Thickness (mm) | Outside diameter of tube or maximum profile section length (mm) |       |       |       |       |       |       |       |      |      |      |       |       |
|---------------------|-----------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|------|------|------|-------|-------|
|                     | 20                                                              | 40    | 60    | 80    | 100   | 120   | 150   | 200   | 300  | 500  | 600  | 700   | 800   |
| 2                   | 14                                                              | 14    | 14    | 14    | 14    | 14    | 10-14 | 10-14 | 8-12 | 8-12 | 6-10 | 5-8   | 5-8   |
| 3                   | 14                                                              | 14    | 10-14 | 10-14 | 10-14 | 10-14 | 8-12  | 8-12  | 6-10 | 6-10 | 5-8  | 5-8   | 5-8   |
| 4                   | 14                                                              | 14    | 10-14 | 10-14 | 8-12  | 8-12  | 6-10  | 6-10  | 5-8  | 5-8  | 4-6  | 4-6   | 4-6   |
| 5                   | 14                                                              | 10-14 | 10-14 | 8-12  | 8-12  | 6-10  | 6-10  | 5-8   | 5-8  | 4-6  | 4-6  | 4-6   | 4-6   |
| 6                   | 14                                                              | 10-14 | 10-14 | 8-12  | 8-12  | 6-10  | 6-10  | 5-8   | 5-8  | 4-6  | 4-6  | 3-4   | 3-4   |
| 8                   | 14                                                              | 10-14 | 8-12  | 8-12  | 6-10  | 6-10  | 5-8   | 5-8   | 4-6  | 4-6  | 3-4  | 3-4   | 3-4   |
| 10                  |                                                                 | 8-12  | 8-12  | 6-10  | 6-10  | 5-8   | 5-8   | 4-6   | 4-6  | 3-4  | 3-4  | 3-4   | 3-4   |
| 12                  |                                                                 | 8-12  | 6-10  | 6-10  | 5-8   | 5-8   | 4-6   | 4-6   | 3-4  | 3-4  | 3-4  | 3-4   | 2-3   |
| 15                  |                                                                 |       | 6-10  | 5-8   | 5-8   | 4-6   | 4-6   | 4-6   | 3-4  | 3-4  | 3-4  | 2-3   | 2-3   |
| 20                  |                                                                 |       |       | 5-8   | 4-6   | 4-6   | 4-6   | 3-4   | 3-4  | 2-3  | 2-3  | 2-3   | 2-3   |
| 30                  |                                                                 |       |       |       | 4-6   | 4-6   | 3-4   | 3-4   | 3-4  | 2-3  | 2-3  | 2-3   | 2-3   |
| 50                  |                                                                 |       |       |       |       | 3-4   | 3-4   | 3-4   | 2-3  | 2-3  | 2-3  | 2-3   | 2-3   |
| 75                  |                                                                 |       |       |       |       |       | 2-3   | 2-3   | 2-3  | 2-3  | 2-3  | 1.4-2 | 1.4-2 |