Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For C5411

Rotary Screw Air Compressor - CPS 900 VS 200

USA Designed & Manufactured in Italy

10 Bar, 29.9CFM, Variable Speed with 200L Tank



Chicago Pneumatic | Made in Italy | 1 YEAR WARRANTY | NO PLUG 415V

On Sale

Ex GST	Inc GST
~~$6,990.00~~	~~$7,689.00~~
$6,850.00	$7,535.00

ORDER CODE:	C5411
MODEL:	CPS 900 VS 200
Free Air Delivery (LPM / CFM):	848 / 29.9
Air Displacement (LPM / CFM):	~
Includes Air Dryer System (Yes / No):	No
Standard Operating Pressure (bar):	10
Air Receiver Tank (Litre):	200
Noise Level (dBA):	63
Transmission Drive (Type):	Variable Speed
Motor power (kW / hp):	7.5 / 10
Motor Voltage (V / Amps):	415
Dimensions (L x W x H) (mm):	1440 x 615 x 1320
Nett Weight (kg):	153

Features

- Variable Speed – Efficient operation with reduced running costs
- Lower Sound levels – Run between 60-63dba which is inline with current silenced units
- High Duty Cycle – Units can be run for extended periods whilst still maintaining FAD
- Cleaner Air delivery – Less oil and contaminates produced in air compared to piston units
- Oil circulation function – Allows Screw compressor to be run at reduced loads – Unlike standard Screw compressors where they need to be under load and keep temp in oil (otherwise oil is quickly contaminated with water - causing possible damage or increased servicing)
- Oil is circulated to maintain heat – Once it reaches temp it opens solenoid and runs through cooler
- Ease Of Servicing - Customer can purchase maintenance packs and they include maintenance instruction online
- Conventional Screw requires regular servicing by technician that can be expensive



Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Specific Features



Right View