Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For D739

1500mm Easson Digital Readout Scale

VS20 Standard Scale

5µm Resolution



On Sale

Ex GST	Inc GST
~~$500.00~~	~~$550.00~~
$430.00	$473.00

ORDER CODE:	D739
MODEL:	~
Type:	VS20 Standard Scale
Travel - Maximum (mm):	1500
Overall Length (L) (mm):	1646
Scale Resolution (µm):	5
Grating Pitch:	~
Accuracy (µm):	±10
Output Signal:	~
Connector:	~
Cable Length (Metre):	5
Working Temperature (°C):	~
Sealing Protection Class:	~
Maximum Speed (M/min):	~
Reference Point:	~
Width x Height (W x H) (mm):	27.5 x 40.1
Backing Support Plate (Yes / No):	No

Description

Easson VS series Glass Grating Linear Transducer: EASSON - Always committed to Quality, Technology & Innovation


Features

- DOUBLE SEAL DESIGNED SCALES:
- The plastic seals of the transducer use an innovative material to offer superior oil resistance, high elastic recovery properties and durability, carefully designed lip geometry offer low slide resistance.

- 100% LASER CALIBRATION:
- All glass grating transducers are individually inspected and calibrated by our in-house laser calibrator to ensure accuracy complies 100% with the specifications.

- ADVANCED OPTICAL MEASURING SYSTEM:
- The slide carrier of the VS series scales, use a five bearing design for optical grating linear transducer which has been proven as the most reliable system design in today's market.
- The glass grating slide-ways are lapped, and JIS standard P5 grade bearings are used to achieve smooth and accurate movement and long working life.

- D.I.Y. INSTALLATION:
- An easy-to-follow D.I.Y. Installation Manual is supplied with each system, complete with illustrations and mounting brackets.



GS20 Series from 1300mm to 3000mm

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

MODEL	VS 10	
Measuring Standard	Glass scale - Gratin	
Optical Detecting System	Transmissive Infrared S	
Slide Carrier System	Vertical five bearing supporting system	45° f suppo
Resolution	5µm	
Measurement Travel (100-1200mm)	Every 50mm per length specification	
Measurement Travel (1300-3000mm)	-	Every length
Accuracy (100-450mm) Accuracy (500-1000mm) Accuracy (1050-1250mm) Accuracy (1300-3000mm)	±3 - ±5µm ±10µm ±10µm -	
Repeatability	2µm	
Hystersis	3µm	
Protection	DIN4	
Power Supply	DC	
Output Signals		

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For D739

Specific Features



DSub9 Male Plug



Pin	TTL Signal	TTL Cable	422A Signal	422A Cable
1	—	—	$\overline{A}$	Yellow
2	0V	Orange	0V	White
3	—	—	$\overline{B}$	Red
4	Gnd	Ground	Gnd	Ground
5	—	—	$\overline{R}$	Black
6	A	Yellow	A	Green
7	5V	Red	5V	Brown
8	B	Green	B	Blue
9	R	Brown	R	Gray

Dsub9 Wiring Diagram



DIY Installation



Parts



Close Up

Recommended Accessories

D709
Easson Scales - Extension Cable



D710
Easson Scales - Extension Cable



D772
Digital Readout Scale Mounting Bracket Kit



D711
Adaptor Cable



Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For D739

D712

Adaptor Cable

