

Product Brochure For K057A

Hydraulic NC Guillotine & NC Pressbrake Package Deal - HG-1060B & PB-70B

Guillotine - 3100 x 6mm, Pressbrake 3200mm x 70 Ton

Guillotine Ezy-Set NC-89 Control, Pressbrake Estun E21 NC Control



ORDER CODE:	K057A
MODEL:	HG-1060B & PB-70B
Shearing Capacity - Mild Steel (mm):	6
Shearing Capacity - Stainless Steel (mm):	3
Shearing Length (mm):	3100
NC Control (Type):	~
Backgauge (Type):	~
Backgauge Travel (mm):	700 / 600
Pneumatic Sheet Supports:	~
Quick Action Blade Clearance Adjustment:	Yes
Strokes / min (SPM):	12
Blade Angle (deg):	2° 30
Throat Depth (mm):	~
Motor Power (kW / hp):	7.5 / 10 - 5.5 / 7.5
Voltage / Amperage (V / amp):	415
Floor Space Requirements (L x W x H) (mm):	~
Nett Weight (kg):	10170

METALMASTER



Features

- HG-1060B GUILLOTINE: 3100mm x 6mm
- 3100mm x 6mm cutting capacity
- 7.5kW / 10hp 415V motor
- Ezy-Set NC-89 Go-To digital display controlled backgauge with DRO counter
- Quick action blade clearance adjustment for shearing material 1 - 6mm
- Hydraulic material clamping for accurate shearing
- One shot lubrication pump & reservoir for slidenway protection
- Squaring arm incorporating flip over stops
- Roving foot pedal control
- Clamp beam design allows clear view to shadow line on material
- Blades made from 9CrSi material suitable for cutting stainless steel
- Plate support tables with transfer balls for quick & easy material alignment and manoeuvrability
- Front sheet supports with ball bearing guides preventing material damage when setting up
- Safety three photo electric light beams on rear guarding
- Safety reset rear guarding button mounted to back of electrical box
- Heavy duty under driven machine construction
- Equipped with shadow line lighting-alignment device
- Mild steel capacity is rated on hot rolled material with 250MPA
- PB-70B PRESSBRAKE: 3200 x 70 Ton
- Hydraulic / Mechanical ram, synchronised positive stop design, ram stroke controlled by precision mechanical nut depth stops built into each cylinder. Electronically controlled by Estun NC-E21 digital control assuring accurate repeatability.
- Parallelism is ensured by torsion bar that can be easily adjusted by clutch system.
- Estun NC-E21 programmable digital control stores up to 40 unique programs with 25 automatic progressive bending steps in each individual program, assuring production accuracy & repeatability every time.
- Estun NC-E21 programmable hardened ballscrew backgauge system, simply enter the desired measurement into the controller and press go, the backgauge then will move quickly into the position you have requested. The superior hardened ballscrew system eliminates any backlash that leadscrew type machines produce.
- Segmented heavy duty 35° offset top punch is segmented for return bend clearance, complete with European style punch holder with an adjustable wedge clamping system for crowning. Intermediate clamp has safety key to stop punch dropping.
- Multi vee ("V") bottom die is made from one 3200mm solid die block design to handle heavy plate, safety edge vee ("V") is incorporated in bottom die block.
- Conveniently mounted control box on pendant for quick swivel and adjustments.
- Mono-block steel frame design, welded then machined to ensure minimal bed deflection under load

Product Brochure For K057A

- Enclosed rear gate with micro safety switches complete with sliding rear door for easy access.
- European Intermediate clamping system, allowing operator to change position of tooling to suit multiple requirements on complex applications. This feature ensures minimum down time, more productivity and results in reduced cost per finished product.
- Sliding steel fabricated sheet supports enabling a wide range of material sizes to be aligned and supported at the correct required height. This feature is achieved with a "T" slot machined down the total length of the die bed; sheet supports are also adjustable vertically to assist in supporting material with return bends already folded.
- Adjustable sliding blocks control the machines beam to provide desirable open height distance to the (slow speed) mute bending point. Operator adjustable locking knobs for quick adjustment, enables accurate repeatability and increased productivity.
- Metal safety guarding surrounding the machine with rear sliding door fitted and micro switch ensuring operator safety. Clear access panels placed at each end of machine allows the operator to clearly view tooling and work piece during bending operation. MetalMaster specially design gates to suit Australian safety requirements.
- Hydraulic MPA pressure gauge mounted on right side of support frame with quick adjusting pressure control knob allowing operator to accurately set the pressure required for different material thickness, incorporating with hydraulic overload protection.
- Welded steel fabricated synchronised torsion bar horizontally supporting main bending beam to provide consistent parallelism that also can be adjusted for taper correction.
- The vertical supporting slides are treated to provide greater wear resistance and increased accuracy.
- Includes safety control guarding system with light curtains fitted
- Mild steel capacity is rated on hot rolled material with 250MPA.

Includes

- HG-1060B GUILLOTINE:
 - Rapid blade gap adjustment
 - Emergency stops fitted on both ends of machine for additional safety
 - Shadow line lighting allows operator to quickly see the cut line
 - 700mm Ezy-Set NC-89 Go-To via backgauge with fine adjustment
 - Swing away backgauge function for cutting long sheets
 - 4 edge quality 9CrSi blades suitable for stainless steel
 - Transfer balls on table & support arms
 - Heavy duty support arms and squaring arms
 - Stroke counter and short stroke adjustment
 - Sliding chute fitted, easily allowing operator to retrieve cut pieces
 - Three safety photo electric light beams on rear guarding
- PB-70B PRESSBRAKE:
 - Swivel pendant control unit operated by Estun NC-E21 control
 - Sliding front sheet support arms
 - Emergency stop buttons conveniently located on control panel and foot control
 - Mobile dual operation foot control
 - Segmented 35° offset top punch
 - Solid one piece four way multi vee (V) die block
 - Top punch tool intermediate holder system with wedge type adjustment
 - Powered hardened ballscrew backgauge with 600mm travel, operated by Estun NC-E21 control
 - Oil tank level indicator
 - Metal constructed safety guarding surrounding machine with clear side viewing panels
 - Integrated hydraulic system allowing rapid approach switching automatically to slow bend.

Specific Features



HG 1060B Guillotine



NC 89 Control Panel



Right View



NC 89 Backgauge DRO

Product Brochure For K057A



Quick Action Blade Adjustment



Squaring Arm



Squaring Arm with Flip Over Stop



Front Sheet Supports with Roller Bearings



Material Transfer Ball On the Table



Motorised Backgauge



Motorised Backgauge Close Up



Motorised Backgauge Right View



Back Gauge Drive Motor



Micro Switches



3 Safety Photo Sensors



Safety Omron E3ZS Rear Light Sensor Guarding



Rear Guard Reset Button



Emergency Stop Switch



One Shot Lubrication



Mobile Foot Control

Product Brochure For K057A



Shown with Optional Ball Transfer Tables - Order Code (L840)



Quick Action Blade Clearance Adjustment



PB 70B Pressbrake



E21 New NC Programmable Controller




E21 New Estun



Adjustable Travel Limit Control



Enclosed Rear Safety Guarding



Top and Bottom Tooling



Intermediate Clamps



Adjustable and Sliding Front Sheet Supports



Adjustable Pressure Control




Estun NC E21 Control Back Gauge




Mobile Foot Control



Controller Top View



Adjustable Top Tool Taper Wedge System



Fine Adjustment Beam Positioning

Product Brochure For K057A




Fine Adjust Back Gauge




Synchronised Torsion Bar




Synchronised Torsion Bar




Lubrication Chart



Tonnage Calculation Chart



Segmented Top Punch



One Piece 4 Sided Die

Recommended Accessories

M800

Rubber Mat - Anti-Fatigue

M805


Rubber Mat - Anti-Fatigue

O000

SpillFix Universal Organic Absorbent

O043

Rust & Corrosion Preventive



Product Brochure For K057A

O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive



O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

