

Product Brochure For K8101

19" Wood Band Saw - BP-480CE, 415V

Built to School Specifications
 NSW DOE Item 1B

Please Call



ORDER CODE:	K8101
NSW DOE Item No.:	1B
QLD DOE Item No.:	~
MODEL:	Schools / TAFE BP-480
Throat Capacity (mm):	462
Wheel Diameter (mm):	480
Height Capacity (mm):	310
Table Size (mm):	480 x 480
Frame Type:	Steel
Motor Power (kW / hp):	1.5 / 2
Voltage / Amperage (V / amp):	415
Full Height (mm):	1980
Blade Code:	W434A/B
Blade Length (mm):	3630 x 19
Net Weight (kg):	174



Description

The Hafco Woodmaster BP-480CE Bandsaw has been professionally upgraded to meet the specific safety and operational requirements set by the NSW Department of Education. Modifications include upgraded switchgear, emergency stop systems, and enhanced safety controls to ensure compliance with current school-based risk management standards. Each unit is carefully inspected and certified for use in NSW school environments, providing peace of mind for educators and administrators.

Manufactured in Taiwan, the CE Safety Compliant BP-480 is powered by a robust 1.5kW (2hp) brake motor and delivers a cutting capacity of 465mm depth x 310mm height. Balanced Ø480mm cast iron blade wheels reduce vibration for smoother operation, while dual blade speeds (488 & 1010m/min) provide versatility for both heavy-duty and precision tasks.

For over 40 years, Hare & Forbes Machineryhouse has proudly partnered with schools, TAFEs, and trade training centres across Australia, supplying a wide range of machinery. Throughout this time, we have developed an in-depth understanding of each state's unique requirements, enabling us to deliver tailored, compliant solutions for your next machinery purchase.

Features

- Quality Taiwanese manufacture
- Powerful 2hp - 415V braked motor - CE Safety Compliant
- 465mm throat capacity
- Extra high cutting capacity - 310mm
- Ø480mm heavy duty cast iron wheels
- Two blade speeds 488/1010m/min
- Large cast iron table tilts to -5° to +45°
- High / Low ripping fence - 150mm & 12mm
- Double ball bearing guides with grooved rear thrust bearing for maximum blade support
- Quick-action blade tension
- Rack & pinion adjustment on top blade guide
- Two viewing windows make blade tracking and tensioning possible while the machine is running
- Twin Ø100mm (4") dust ports for efficient dust extraction

Safety Features


- Braked motor - CE safety compliant stopping time
- Keyed brake release enhances safety during blade changes
- Magnetic NVR on/off switch
- Emergency stop switch
- Micro-switch protection on hinged blade guard doors

Product Brochure For K8101

- Keyed isolation switch - PWD approved
- Please Note:
- This machine is not supplied with a 415 volt plug & lead

Includes

- High / Low ripping fence
- Mitre gauge
- 6TPI, Blade - 3630 x 19 x 0.8mm



Specific Features



Rear View



Shown With Blade Door Open



Blade Adjustment



Cast Iron Blade Wheels



Ball Bearing Blade Guides



Cast Iron Table Tilts To 45 Degrees



Rack Pinion Adjustment On Top Blade Guide



Keyed Safety Switch

Product Brochure For K8101




Sliding Rip Fence



Mitre Guide



Table Tilt Adjustment



Blade Tension Site Indicator



Large Cast Iron Table



Safety Micro Switch On Door

Recommended Accessories

W434A

Wood Band Saw Blade - 6TPI,
 Blade - 3630 x 19 x 0.8mm

W434B

Wood Band Saw Blade - 3TPI,
 Blade - 3630 x 19 x 0.8mm

W309

Safety Push Blocks & Stick Set

W311

Ripping Gauge



Product Brochure For K8101

W3130

Twin Feather Board Set



W344

Wood Dust Accessory Kit

