Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For K8158

# Oscillating Belt Sander - Slik 7.0b, 240V

Built to School Specifications
NSW DOE Item 10A




## Please Call

| | |
|---|---|
| ORDER CODE: | K8158 |
| NSW DOE Item No.: | 10A |
| QLD DOE Item No.: | ~ |
| MODEL: | Schools / TAFE Slik 7.0b |
| Disc Diameter (mm): | ~ |
| Variable Table Feed Speed (m/min): | ~ |
| Sanding Drum Speed (rpm): | ~ |
| Belt Size (mm): | 2515 x 150 |
| Drum Diameter (mm): | ~ |
| Max Sanding Width (mm): | ~ |
| Max Sanding Thickness (mm): | ~ |
| Min Sanding Thickness (mm): | ~ |
| Dust Collector Ports (No. x mm): | ~ |
| Feed Motor Power (hp): | ~ |
| Motor Power (kW / hp): | 2.2 / 3 |
| Voltage / Amperage (V / amp): | 240 / 15 |
| Nett Weight: | 185 |

scheppach

2 YEAR WARRANTY

15A PLUG 240V

### Features

- Oscillating sander with graphite pad for smooth operation
- Easy belt tracking adjustment
- Rear material guide stop
- 90 ~ 180º tilting sanding belt
- 2515mm x 150mm belt with 16M/sec belt speed
- 90 ~ 40º tilting cast iron side table
- 850 x 300mm cast iron side table with 90mm height adjustment
- Table height adjustment via hand wheel located in convenient location
- 300 x 245mm cast iron end table with 130mm height adjustment
- 2.2kW / 3hp, 2800rpm, 240V direct drive motor
- Ø100mm (4") dust ports for efficient dust extraction
- Cabinet storage stand

### Safety Features

- DOL starter switch with overload protection and raised red stop button
- Keyed isolation switch - PWD approved
- Test and tag certificate on 240V lead

### Includes

- Cabinet storage stand
- End & side cast iron tables
- Spare linishing belts
- Mitre guide
- Table guide support