

Product Brochure For K84506

140 Amp STICK & DC TIG Welder - RAZOR ARC 140

Supplied to School Specifications
 NSW DOE Item 42A

Please Call



ORDER CODE:	K84506
NSW DOE Item No.:	42A
QLD DOE Item No.:	~
MODEL:	NSW Schools / TAFE & RAZOR™ ARC 140
Voltage (V / amp):	240V / 10
Rated Duty Cycle In 10 Min (TIG) 40°C (% @ amp):	35%@140
Rated Duty Cycle In 10 Min (MMA) 40°C (% @ amp):	15%@140
Rated Output Current (amp):	10 - 140
Weldable Stick Electrode (mm):	3
Hot Start:	Yes
Anti Sticking:	Yes
Arc Force:	Yes
TIG Ignition:	Lift Arc
Dimensions (mm):	313 x 250 x 130
Nett Weight (kg):	4.7



Description

This powerful, professional STICK (MMA) welding machine is built for both the worksite and workshop. It's loaded with advanced features like hot start, arc force, and anti-stick for optimal performance. Plus, its DC Lift Arc TIG capability adds versatility to tackle a variety of welding tasks.

HD Backlit Interface

This next generation interface panel is bright and easy to read in any environment.

10A Plug

A 10 AMP power plug can be used on any domestic outlet. It's perfect for the DIY home handyman or the professional welder looking for a machine that can be used almost anywhere.

DC Lift Arc TIG

Lift Arc ignition allows the arc to be started easily in DC TIG by simply touching the tungsten to the workpiece and lifting it up to start the arc. This stops the tungsten tip sticking to the workpiece and breaking the tip from the tungsten electrode.

Smart Fan

Smart Fan diminishes noise, saves power, helps reduce energy costs, and minimises the number of contaminants being pulled through the machine.

Advanced MMA Features

This machine features Anti-Stick technology, as well as adjustable Arc Force and Hot Start functionality. These features are designed for improving weld quality and ease of use.

Generator Compatible

Going off the grid? The RAZOR ARC 140 can be connected to a generator, we recommend one with an 8kVA rating.

Lightweight & Portable

Weighing just 5.5kg, the RAZOR ARC 140 is ready to go anywhere you need it.

Features

- Thermal overload protection
- 10 Amp plug - Connect to a 10 Amp outlet
- Complies to AS/NZS 60974.1 standards
- UNIMIG is pleased to offer a 5-year warranty on the RAZOR ARC 140

Product Brochure For K84506

Includes

- RAZOR ARC 140 PFC Welder
- 4m Twist Lock Electrode Holder
- 4m 300 Amp Earth Clamp & Lead
- Operating Manual
- Professional Leather Welding Gloves
- Chipping Hammer

Optional Accessories

- Argon Gas Regulator with Bobbin Flowmeter
- 17V TIG Welding Torch

Specific Features



Front



Full Kit



Professional Leather Welding Gloves



Chipping Hammer

Recommended Accessories

W10361

Magnetic TIG Torch Rest



W241

Universal Welder Trolley



W170A

Air Cooled TIG Welding Torch



W119

Anti-Spatter Spray



Product Brochure For K84506

O0184

Ar/O2 - Argon 98% & Oxygen 2% Disposable Cylinder



O0185

CO2/Ar - 86% Argon & 14% Carbon Dioxide Disposable Cylinder



O300

Gas Refillable Cylinder



O304

Gas Refillable Cylinder



O3045

Gas Refillable Cylinder



O302

Gas Refillable Cylinder



O306

Gas Refillable Cylinder



O3065

Gas Refillable Cylinder



O0171

Argon Gas Regulator



W161

Argon Gas Regulator-Bobbin Flowmeter



W160A

Argon Gas Regulator-Twin Gauge



W590

1.6mm Tig Tungsten Electrode - Zirconiated White



Product Brochure For K84506

W596

2.4mm Tig Tungsten Electrode - Zirconiated White



W597

1.6mm Tig Tungsten Electrode - Ceriated Grey



W598

2.4mm Tig Tungsten Electrode - Ceriated Grey



W001

Auto Darken Welding Helmet - 9-13 Shade



W002

Auto Darken Welding Helmet - 9-13 Shade



W1000A

Promax HV5 Welding Jacket



W1001A

Promax Blue FR Welding Jacket



W1002A

Professional Promax BL7 Welding Jacket




W100

ROGUE™ Heavy Duty Welding Gloves - 400mm



L3456

How to Weld Book



W225

Welding Curtain



W125

Ø1.6mm TIG Filler Rod - Mild Steel



Product Brochure For K84506

W126

Ø2.4mm TIG Filler Rod - Mild Steel



W127

Ø1.6mm TIG Filler Rod - Stainless Steel



W128

Ø2.4mm TIG Filler Rod - Stainless Steel

