

## Product Brochure For L1296

### Twin Drum Sander - DS-660

Variable Conveyor Feed Speeds

660 x 127mm (W x H) Material Capacity



| Ex GST            | Inc GST           |
|-------------------|-------------------|
| <b>\$2,990.00</b> | <b>\$3,289.00</b> |

|                                          |                   |
|------------------------------------------|-------------------|
| ORDER CODE:                              | L1296             |
| MODEL:                                   | DS-660            |
| Variable Table Feed Speed (m/min):       | 0.93 - 6.2        |
| Sanding Drum Speed (rpm):                | 1280              |
| Belt Size (mm):                          | ~                 |
| Drum Diameter (mm):                      | 125               |
| Maximum Material Width (mm):             | 660               |
| Maximum Material Thickness (mm):         | 127               |
| Minimum Material Thickness (mm):         | 6                 |
| Dust Collector Port Diameter (Qty x mm): | 2 x Ø100          |
| Feed Motor Power (hp):                   | 1/6               |
| Motor Power (kW / hp):                   | 2.2 / 3           |
| Voltage / Amperage (V / amp):            | 240               |
| Floor Space (W x D x H) (mm):            | 787 x 1168 x 1346 |
| Nett Weight (kg):                        | 223               |



#### Description

The DS-660 features a powerful 3HP/ 240V single-phase motor giving this machine a plenty of power to suit most sanding applications. With a variable speed rubberised feed belt that helps to protect the underside of panels during sanding making this a versatile machine. The abrasive material is spirally wound onto both drums with the option for the drums to be configured with a coarse paper on the front drum and fine paper on the rear to save you time while reducing the need for prolonged hand sanding.

#### Features

- 660mm (26") sanding width capacity
- Twin, dynamically balanced 125mm drums ensure smooth sanding (1 coarse & 1 fine)
- High quality conveyor belt, easy to track for smooth feeding
- Variable speed conveyor drive giving 0.92 m/min to 6.2 m/min
- Sanding workpiece thickness, Min/Max (6 - 127mm)
- Heavy duty 2.2kW / 3hp Induction 240V motor
- Twin Ø100mm (4") dust ports for efficient dust extraction

#### Includes

- 2 x Abrasive belts (80 grit & 120 grit)

## Product Brochure For L1296

### Specific Features



Belt Tension Adjustment



Twin 100mm Dust Ports



Height Adjustment Handle



Electronic Height Reader



Sanding Drums



Drum Adjustment



Control Panel



Rear View



Side View



Left Side View

## Product Brochure For L1296

### Recommended Accessories

A95408

Drum Sander - Belt



A95412

Drum Sander - Belt



A95424

Drum Sander - Belt



G183

Abrasive Belt & Disc Cleaning Stick



W394

Dust Collector



W329

Dust Collector



W344

Wood Dust Accessory Kit



W334

Dust Hose Reducer



## Product Brochure For L1296

**W333**

Dust Hose Reducer



**W335**

Blast Gate



**W336**

Dust Hose Elbow - 90 Degree



**W337**

Dust Hose Y Adaptor



**W338**

Dust Hose Universal Dust Hood



**W339**

Dust Hose Floor Sweeper Attachment



**W340**

Dust Hose Clamp

