

Product Brochure For L172

Centre Lathe - CL-100

660 x 2000mm Turning Capacity
 Includes Taper Turning Attachment



| | |
|---|---------------|
| ORDER CODE: | L172 |
| MODEL: | CL-100 |
| Swing Over Bed (mm): | 660 |
| Distance Between Centres (mm): | 2000 |
| Spindle Bore (mm): | 105 |
| Swing In Gap (mm): | 870 |
| Swing Over Cross-slide (mm): | 380 |
| Digital Readout System Fitted: | Optional |
| Quick Change Toolpost Fitted: | Optional |
| Leadscrew Covers Fitted: | ~ |
| Taper Turning Attachment: | Yes |
| Coolant System: | Yes |
| Tool Height To Suit (mm): | 25 |
| Centre Height (mm): | 330 |
| Spindle Nose Size or Type: | D1-8 Camlock |
| Bed Width (mm): | 390 |
| Headstock Spindle Taper (MT): | 1-20, 120 |
| Tailstock Taper (MT): | 5 |
| Cross Slide Travel (mm): | 370 |
| Compound Slide Travel (mm): | 190 |
| Leadscrew Type: | Metric |
| Metric Cross Feed (X-Axis) (mm/rev): | 0.027 - 2.73 |
| Imperial Cross Feed (X-Axis) (inch/rev): | ~ |
| Metric Longitudinal Feed (Z-Axis) (mm/rev): | 0.063 - 6.43 |
| Imperial Longitudinal Feed (Z-Axis) (inch/rev): | ~ |
| Metric Thread Steps & Pitch (No. / mm): | 1/8 - 28 |
| Imperial Thread Steps & TPI (No. / TPI): | 1 - 224 |
| 3 Jaw Chuck Diameter (mm): | 325 |
| 4 Jaw Chuck Diameter (mm): | 400 |
| Spindle Steps / Speeds (No. / rpm): | 24 (6 - 1120) |
| Motor Power (kW / hp): | 11.25 / 15 |
| Voltage / Amperage (V / amp): | 415 |
| Nett Weight (kg): | 3350 |

Features

- Taper turning attachment fitted to saddle
- Twin bearings supporting headstock spindle
- Adjustable taper roller bearings providing spindle accuracy
- Precision 'V'-beds & headstock gears are all hardened & ground
- Multiple discs forward and reversing clutch system
- Overload protection on drive motor and coolant system
- Universal enclosed gearbox incorporating metric & imperial thread capabilities
- Foot operated spindle brake with safety cut out switch
- X & Z axis rapid traverse selection lever incorporated on the saddle @ 4.5m/min
- 390mm wide induction hardened heavy duty cast iron bed
- Removable gap bed allowing work piece to swing up to 870mm
- Slide out swarf trays accessible from rear of machine
- Two speed tail stock selector
- Powered longitudinal and cross feeds
- Dual calibrated dials incorporating metric & imperial graduations
- Coolant system with flexible hose enabling operator to manipulate flow direction
- Oil sight glass for head stock and gearbox & apron
- Low voltage halogen work light
- D1-8 camlock spindle for quick chuck removal
- 24 spindle speeds 6-1120rpm
- Large 105mm spindle bore
- 11.25kW / 15HP 415V main motor

Product Brochure For L172

Includes

- Taper Turning Attachment
- 325mm 3-jaw chuck with reverse jaws
- 400mm 4-jaw chuck
- Faceplate
- Fixed Steady with roller bearings
- Travelling steady
- Dead centres
- Thread chasing dial
- Foot brake
- Coolant system
- Work light
- Rear splash guard
- Spindle reducing bush


Recommended Accessories

M800
 Rubber Mat - Anti-Fatigue

M805
 Rubber Mat - Anti-Fatigue

S090A
 Soluble Metal Cutting Fluid - 1
 Litre

S090
 Soluble Metal Cutting Fluid - 5
 Litre



S076
 Cutting Tool Lubricant Fluid -
 500ml

S077
 Drilling, Tapping & Cutting Tool
 Lubricant Spray - 400g

S075
 Cutting Tool Lubricant Paste -
 200g

S074
 Cutting Tool Lubricant Paste -
 500g



Product Brochure For L172

O000

SpillFix Universal Organic Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive

