

Product Brochure For L242

Centre Lathe - AL-1000D

360 x 1000mm Turning Capacity



ORDER CODE:	L242
MODEL:	AL-1000D
Swing Over Bed (mm):	356
Distance Between Centres (mm):	1000
Spindle Bore (mm):	40
Swing In Gap (mm):	516
Swing Over Cross-slide (mm):	225
Digital Readout System Fitted:	Optional
Quick Change Toolpost Fitted:	Optional
Leadscrew Covers Fitted:	~
Taper Turning Attachment:	~
Coolant System:	Yes
Tool Height To Suit (mm):	16
Centre Height (mm):	178
Spindle Nose Size or Type:	D1-4 Camlock
Bed Width (mm):	190
Headstock Spindle Taper (MT):	5
Tailstock Taper (MT):	3
Cross Slide Travel (mm):	175
Compound Slide Travel (mm):	100
Leadscrew Type:	Metric
Metric Cross Feed (X-Axis) (mm/rev):	0.033 - 0.468
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	0.066 - 0.936
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	30 (0.4 - 7.0)
Imperial Thread Steps & TPI (No. / TPI):	32 (4 - 56)
3 Jaw Chuck Diameter (mm):	160
4 Jaw Chuck Diameter (mm):	200
Spindle Steps / Speeds (No. / rpm):	18 (50 - 2000)
Motor Power (kW / hp):	2.25 / 3
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	720

Description

Manufactured in Taiwan

Features

- Tool room quality precision lathe, Made in Taiwan and have been sold for over 20 years
- Gear drive headstock for quick change of spindle speeds
- Nachi Japanese made bearings supporting headstock spindle
- Stand increasing rigidity and reducing vibration
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Foot operated spindle brake with safety cut out switch
- Change gears for metric and imperial thread cutting
- Oil sight glass for head stock and gearbox
- Adjustable taper roller bearings support the spindle
- Overload clutch mechanism on auto power feed
- Overload protection on drive motor and coolant system
- 3hp 415V motor, 18-speed (50 - 2000rpm)
- Inching button is incorporated on the control panel for convenient spindle speed selection
- Enclosed quick action gearbox for thread cutting and auto feeding
- Powered longitudinal and cross feeds
- D1-4 camlock spindle for quick chuck changes and safe reverse-direction turning. ISO standard
- Removable gap bed-way for larger diameter jobs
- Dual calibrated dials (except for saddle hand wheel)

Product Brochure For L242

- Coolant system with flexible hose
- Slide out swarf tray

Includes

- 160mm 3-jaw chuck with reverse jaws
- 200mm 4-jaw chuck
- Faceplate
- Fixed Steady
- Travelling Steady
- Change gears
- Dead centres
- Thread-chasing dial
- Stand
- Foot brake
- Rear splash guard & swarf tray
- Toolbox
- Instruction booklet


Specific Features



Gear Box Controls



Control Panel



Speed Chart



Thread Chart



Tool Post




Saddle



Tailstock



Cross Dial



Compound Dial



3 Point Travelling Steady




Thread Chasing Dial



Travelling Steady

Product Brochure For L242



GEAR	PITCH	SCALE
18T	0.45	0.9
	2.25	4.5
	0.25	0.5
	0.75	1
	1.5	2
20T	1.25	2.5
	5	1, 4
	1.75	3.5
21T	7	1, 3, 5
21T	0.7	1, 4

Thread Chasing Chart



Compound Scale

Recommended Accessories

G660

Lathe Leadscrew Cover Kit



G659

Lathe Leadscrew Cover Kit - Concertina



L258

Taper Turning Attachment



C052

3MT Live Centre



L0077

Lathe Turning Tool Kit - 7 piece Insert Type



L451

Lathe Turning Tool Kit - 3 piece Insert Type



L457

Lathe Threading Tool Kit - Insert Type



L465


Professional Lathe Parting Tool Kit - Insert Type



Product Brochure For L242


L341

Fitting and Machining Technical Book



L3455

Professional Sheet Metal Fabrication Book



L295

Quick Change Toolpost



L295A

Quick Change Toolpost Holder - Std



L076

Knurling Tool Holder Kit



L277

Vertical Mill Slide



D126

Metric 135° Precision HSS Drill Set - 170 Pieces



D1282

Imperial 135° Precision HSS Drill Set - 29 Piece



C980

5C Collet Lathe Adaptor



C294

Industrial Drill Chuck - Keyless Type



D443A

3MT x JT3 Drill Chuck Arbor Type



D719

150mm Easson Digital Readout Scale



Product Brochure For L242

D734

900mm Easson Digital Readout Scale




M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



S090A

Soluble Metal Cutting Fluid - 1 Litre



S090

Soluble Metal Cutting Fluid - 5 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste - 200g



S074

Cutting Tool Lubricant Paste - 500g



O000

SpillFix Universal Organic Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



0040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive

