

Product Brochure For L243

AL-1340 Centre Lathe - Schools / TAFE

330 x 1000mm Turning Capacity



ORDER CODE:	L243
NSW DOE Item No.:	~
QLD DOE Item No.:	~
MODEL:	Schools/TAFE AL-1340
Digital Readout:	Optional
Tool To Suit (mm):	16
Distance Between Centres (mm):	1000
Swing Over Bed (mm):	330
Swing Over Gap (mm):	490
Swing Over Cross-slide (mm):	200
Centre Height (mm):	165
Spindle Bore (mm):	Ø40
Camlock Spindle Size:	D1-4
Bed Width (mm):	190
Head Stock Spindle Taper (MT):	5
Tail Stock Taper (MT):	3
Cross Slide Travel (mm):	175
Compound Slide Travel (mm):	100
Lead Screw:	Metric
Cross Feed (mm/rev):	0.034 ~ 0.468
Longitudinal Feed (mm/rev):	0.068 ~ 0.936
Metric Thread Range (No. / mm):	30 (0.4 - 7.0)
Imperial Thread Range (No. / TPI):	32 (4 - 56)
3 Jaw Chuck Diameter (mm):	Ø160
4 Jaw Chuck Diameter (mm):	Ø200
Spindle Steps/speeds (No. / RPM):	9 / 82-2000
Motor Power (kW / hp):	2.25 / 3
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	700

Description

We for many years have been working in close consultation with the education departments to ensure the most suitable equipment is provided to our schools and TAFE, not only does it comply with the departments stringent safety requirements but is built to last the distance. That's why we consider our company to be a specialist when it comes to supplying quality Wood Work and Metal Working Machinery for Public or Private Schools, TAFE Colleges and Trade Training Centres in all states of Australia.

The AL-1340 is manufactured in Taiwan with all the safety features needed to comply with the education department. This machine has the following safety features such as leadscrew cover, chuck guard with micro switch, micro switch fitted to side access door and emergency foot brake making this machine superior in safety to protect the learning and developing students.

Features

- Tool room quality precision lathe, Made in Taiwan and have been sold for over 20 years
- Gear drive headstock for quick change of spindle speeds
- Stand increasing rigidity and reducing vibration
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Foot operated spindle brake with safety cut out switch
- Chuck guard fitted with micro switch
- Leadscrew cover ensures swarf not reaching clasp nut
- Change gears for metric and imperial thread cutting
- Oil sight glass for head stock and gearbox
- Adjustable taper roller bearings support the spindle
- Overload clutch mechanism on auto power feed
- Overload protection on drive motor and coolant system
- 3HP/415V motor, 9-speed (82 - 2000rpm)
- Inching button is incorporated on the control panel for convenient spindle speed selection
- Enclosed quick action gearbox for thread cutting and auto feeding
- Powered longitudinal and cross feeds
- D1-4 camlock spindle for quick chuck changes and safe reverse-direction turning. ISO standard
- Removable gap bed-way for larger diameter jobs
- Dual calibrated dials
- Coolant system with flexible hose
- Slide out swarf tray

Product Brochure For L243

Includes

- 3-jaw chuck with reverse jaws
- 4-jaw chuck
- Faceplate
- Fixed Steady
- Travelling steady
- Chuck guard
- Leadscrew covers
- Dead centre
- Thread chasing dial
- Foot brake
- Coolant system
- Rear splash guard
- Instruction booklet

Specific Features



Safety Chuck Guard



Sliding drip tray for swarf removal



Footbrake



Leadscrew Covers




Leadscrew Covers



Headstock Controls



Limit Switch



Saddle Controls



Thread Chasing Dial



Toolbox



Feed Charts