

Product Brochure For L245VS

Centre Lathe - AL-1440V

Ø356 x 1000mm Turning Capacity - Ø51mm Spindle Bore
 Includes Digital Readout System & Electronic Variable Speed With
 Digital Speed Display

Back In Stock Soon

Ex GST

Inc GST

\$17,250.00 \$18,975.00



ORDER CODE:	L245VS
MODEL:	AL-1440V
Swing Over Bed (mm):	356
Distance Between Centres (mm):	1000
Spindle Bore (mm):	51
Swing In Gap (mm):	516
Swing Over Cross-slide (mm):	225
Digital Readout System Fitted:	Yes
Quick Change Toolpost Fitted:	Optional
Leadscrew Covers Fitted:	Yes
Taper Turning Attachment:	Optional
Coolant System:	Yes
Tool Height To Suit (mm):	16
Centre Height (mm):	178
Spindle Nose Size or Type:	D1-5 Camlock
Bed Width (mm):	230
Headstock Spindle Taper (MT):	6
Tailstock Taper (MT):	3
Cross Slide Travel (mm):	175
Compound Slide Travel (mm):	100
Leadscrew Type:	Metric
Metric Cross Feed (X-Axis) (mm/rev):	0.033 - 0.467
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	0.066 - 0.935
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	32 (0.4 - 7.0)
Imperial Thread Steps & TPI (No. / TPI):	32 (4 - 56)
3 Jaw Chuck Diameter (mm):	200
4 Jaw Chuck Diameter (mm):	200
Spindle Steps / Speeds (No. / rpm):	Variable (30 - 2200)
Motor Power (kW / hp):	3.75 / 5
Voltage / Amperage (V / amp):	240 / 15
Nett Weight (kg):	840

Description

Toolroom-quality precision lathe, made in Taiwan by the same manufacturer as the renowned AL-960B & AL-1000C/D models.

Features

- Yasakawa Electric Varispeed high-performance, Low-noise, Inverter drive
- Variable speed 30-2200rpm with high/low speed selector
- Nachi Japanese made, adjustable taper roller bearings support the spindle
- 51mm spindle bore
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- One piece heavy steel fabricated stand
- Chuck guard with safety micro switch cut out
- Foot operated spindle brake with safety cut out switch
- 230mm wide induction hardened heavy duty cast iron bed
- Removable gap bed-way for larger diameter jobs
- Powered longitudinal and cross feeds
- Overload clutch mechanism on auto power feed
- Dual calibrated dials (except for saddle hand wheel)
- Enclosed quick action gearbox for thread cutting and auto feeding

Product Brochure For L245VS

- Inching button is incorporated on the control panel
- Coolant system with flexible hose
- Oil sight glass for head stock and gearbox
- Change gears for metric and imperial thread cutting
- D1-5 camlock spindle for quick chuck removal
- Overload protection on drive motor and coolant system
- 3.75kw-5HP - 240V 3 Phase motor (runs on 15amp - 240V power)
- Emergency stop switches fitted to headstock and tailstock plinth

Includes

- 2 axis digital readout system
- 200mm 3-jaw chuck with reverse jaws
- 200mm 4-jaw chuck
- Face plate
- 4-Way toolpost
- Fixed steady
- Travelling steady
- Telescopic leadscrew cover
- Change gears
- Dead centres
- Thread-chasing dial
- Safety chuck guard
- Stand
- Foot brake
- Rear splash guard
- Tool box
- Instruction booklet

Specific Features



3 Axis Digital Readout



Headstock Controls




Control Panel

		PITCH $\frac{1}{60}$ MM									
		M	L	K	L	N	K	J	N	J	
		V	V	V	X	V	X	V	X	X	
A	D	3.2	3.6	4.0	4.5	4.8	5.0	5.6	6.0	7.0	
B	D	1.6	1.8	2.0	2.25	2.4	2.5	2.8	3.0	3.5	
A	C	0.8	0.9	1.0	1.2	1.25	1.4	1.5	1.75		
B	C	0.4	0.45	0.5	0.6	0.6	0.7	0.75			

		FEED $\frac{1}{60}$ INCH									
		P	P	P	P	P	P	P	P	P	
		X	W	V	Y	U					
A	D	0.935	0.831	0.748	0.623	0.534					
B	D	0.467	0.415	0.374	0.311	0.267					
A	C	0.230	0.207	0.187	0.155	0.133					
B	C	0.116	0.103	0.093	0.077	0.066					

Feed Charts




Feeds and Threads Gearbox Levers


		T.P.I. $\frac{1}{60}$ INCH									
		N	M	M	M	M	M	M	M	M	
		Y	W	V	V	V	U	U	U	U	
A	D	4	4 1/2	5	5 1/2	5 3/4	6	6 1/2	7		
B	D	8	9	10	11	11 1/2	12	13	14		
A	C	16	18	20	22	23	24	26	28		
B	C	32	36	40	44	46	48	52	56		

		FEED $\frac{1}{60}$ INCH									
		P	P	P	P	P	P	P	P	P	
		X	W	V	Y	U					
A	D	0.0388	0.0327	0.0294	0.0245	0.021					
B	D	0.0194	0.0163	0.0147	0.0122	0.010					
A	C	0.0092	0.0081	0.0073	0.0061	0.005					
B	C	0.0046	0.0040	0.0036	0.0030	0.002					

Thread Charts



Saddle Controls



Saddle Right View

Product Brochure For L245VS



Thread Chasing Dial



Thread Engagement Lever




Spindle Engagement Lever



3 Point Fixed Steady



2 Point Travelling Steady



Swivel Compound Slide



Compound Slide with 4 Way Toolpost



Compound Slide Dial Graduations



Cross Slide Feed Dial Graduations



Saddle Hand Wheel



Flexible Coolant Hose



3 Jaw Camlock Chuck



Safety Chuck Guard



Tailstock



Tailstock Hand Wheel Dial Graduations




Tailstock Offset Adjustment

Product Brochure For L245VS



Hardened and Ground Bedways



Foot Brake



Toolbox with Accessories



Change Gear Train



Front View



Left View



Left Side View



Rear View



Rear Left View

Product Brochure For L245VS

Recommended Accessories

M002

Steel Machine Mount & Rubber Insert



L258

Taper Turning Attachment



C980

5C Collet Lathe Adaptor



L277

Vertical Mill Slide



L295

Quick Change Toolpost



L017

Right Hand Turning Tool Holder



L018

Left Hand Turning Tool Holder



L044

Right Hand Turning Tool Holder



Product Brochure For L245VS

L045
 Left Hand Turning Tool Holder



L0077
 Lathe Turning Tool Kit - 7 piece
 Insert Type



L451
 Lathe Turning Tool Kit - 3 piece
 Insert Type



L465
 Professional Lathe Parting Tool
 Kit - Insert Type



L457
 Lathe Threading Tool Kit - Insert
 Type



L076
 Knurling Tool Holder Kit



C052
 3MT Live Centre



C045
 3MT Pipe Centre - 70° Cone



C290
 Heavy Duty Drill Chuck - Keyed
 Type



C294
 Industrial Drill Chuck - Keyless
 Type



D443A
 3MT x JT3 Drill Chuck Arbor



D1272
 Metric 135° Precision HSS Drill
 Set - 25 Piece



Product Brochure For L245VS

D1282

Imperial 135° Precision HSS Drill Set - 29 Piece



D126

Metric 135° Precision HSS Drill Set - 170 Pieces



S090A

Soluble Metal Cutting Fluid - 1 Litre



S090

Soluble Metal Cutting Fluid - 5 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste - 200g



S074

Cutting Tool Lubricant Paste - 500g



S091

Soluble Metal Cutting Fluid - 20 Litre



G660

Lathe Leadscrew Cover Kit




G659

Lathe Leadscrew Cover Kit - Concertina




L341

Fitting and Machining Technical Book



Product Brochure For L245VS

L3455
 Professional Sheet Metal Fabrication Book



L300
 Magnetic Swarf Remover




M9991
 Magnetic Floor Sweeper



M800
 Rubber Mat - Anti-Fatigue



M805
 Rubber Mat - Anti-Fatigue



O000
 SpillFix Universal Organic Absorbent



O043
 Rust & Corrosion Preventive



O042
 General Purpose Lubricant & Corrosion Inhibitor



O040
 Rust & Corrosion Preventive



O044
 Rust & Corrosion Preventive

