

Product Brochure For L596

Heavy Duty Centre Lathe - CW61125M

1250 x 5000mm Turning Capacity - 130mm Bore



ORDER CODE:	L596
MODEL:	CW61125M
Swing Over Bed (mm):	1250
Distance Between Centres (mm):	5000
Spindle Bore (mm):	130 (Optional 160)
Swing In Gap (mm):	~
Swing Over Cross-slide (mm):	880
Digital Readout System Fitted:	Optional
Quick Change Toolpost Fitted:	Optional
Leadscrew Covers Fitted:	~
Taper Turning Attachment:	~
Coolant System:	Yes
Tool Height To Suit (mm):	45
Centre Height (mm):	625
Spindle Nose Size or Type:	A2-15 Camlock
Bed Width (mm):	750
Headstock Spindle Taper (MT):	1-20, 140
Tailstock Taper (MT):	6MT with Reducer Sleeve
Cross Slide Travel (mm):	670
Compound Slide Travel (mm):	300
Leadscrew Type:	Metric
Metric Cross Feed (X-Axis) (mm/rev):	0.1 - 12
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	0.05 - 6
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	44 (1 - 120)
Imperial Thread Steps & TPI (No. / TPI):	31 (1/4 - 28)
3 Jaw Chuck Diameter (mm):	~
4 Jaw Chuck Diameter (mm):	1250
Spindle Steps / Speeds (No. / rpm):	21 (3.15 - 315)
Motor Power (kW / hp):	22 / 30
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	15000

Description

Available from 1500 to 8000mm Between Centres

Features

- Triple bearings supporting headstock spindle
- Adjustable taper roller bearings providing spindle accuracy
- Precision 'V'-beds & headstock gears are all hardened & ground
- Hydraulic forward and reversing clutch mechanism with auto braking system
- Overload protection on drive motor and coolant system
- Universal enclosed gearbox incorporating metric & imperial thread capabilities
- X & Z axis rapid traverse selection lever incorporated on the saddle @ 3.8m/min
- 750mm wide induction hardened heavy duty cast iron bed
- Powered longitudinal and cross feeds
- Powered compound slide feed
- Metric calibrated dials
- Coolant system with flexible hose enabling operator to manipulate flow direction
- Lubrication pump on saddle oiling slides
- Oil sight glass for head stock and gearbox & apron
- Slide out swarf trays accessible from rear of machine
- Low voltage halogen work light
- Rack & pinion mechanism assists tail stock movement
- A2-15 spindle nose

Product Brochure For L596

- Adjustable levelling pads
- 21 spindle speeds 3.15-315rpm
- Large 130mm spindle bore
- 22kW / 30HP 415V main motor

Includes

- 1250mm 4-jaw faceplate chuck
- 50-230mm Follow rest
- 50-470mm Steady rest
- Spindle reducing bush
- 2 x dead centres
- Live centre
- Coolant system
- Work light
- Spindle reducing bush

Recommended Accessories


M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



S090A

Soluble Metal Cutting Fluid - 1 Litre



S090

Soluble Metal Cutting Fluid - 5 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste - 200g



S074

Cutting Tool Lubricant Paste - 500g



Product Brochure For L596

O000

SpillFix Universal Organic
Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant &
Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive

