

Product Brochure For L626

Centre Lathe - CL-75

560 x 2000mm Turning Capacity

Includes Taper Turning Attachment



ORDER CODE:	L626
MODEL:	CL-75
Swing Over Bed (mm):	560
Distance Between Centres (mm):	2000
Spindle Bore (mm):	80
Swing In Gap (mm):	785
Swing Over Cross-slide (mm):	350
Digital Readout System Fitted:	Optional
Quick Change Toolpost Fitted:	Optional
Leadscrew Covers Fitted:	~
Taper Turning Attachment:	Yes
Coolant System:	Yes
Tool Height To Suit (mm):	25
Centre Height (mm):	280
Spindle Nose Size or Type:	D1-8 Camlock
Bed Width (mm):	350
Headstock Spindle Taper (MT):	7
Tailstock Taper (MT):	5
Cross Slide Travel (mm):	316
Compound Slide Travel (mm):	130
Leadscrew Type:	Metric
Metric Cross Feed (X-Axis) (mm/rev):	0.020 - 0.573
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	0.059 - 1.646
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	47 (0.2 - 14)
Imperial Thread Steps & TPI (No. / TPI):	60 (2 - 112)
3 Jaw Chuck Diameter (mm):	315
4 Jaw Chuck Diameter (mm):	350
Spindle Steps / Speeds (No. / rpm):	12 (25 - 1600)
Motor Power (kW / hp):	7.5 / 10
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	3100

Features

- Taper turning attachment fitted to saddle
- Triple bearings supporting headstock spindle
- Adjustable taper roller bearings providing spindle accuracy
- Precision 'V'-beds & headstock gears are all hardened & ground
- One piece cast iron base increases rigidity
- Overload protection on drive motor and coolant system
- Universal enclosed gearbox incorporating metric & imperial thread capabilities
- Inching button incorporated on the control panel for convenient spindle speed selection
- Foot operated spindle brake with safety cut out switch
- 350mm wide induction hardened heavy duty cast iron bed
- Removable gap bed allowing work piece to swing up to 785mm
- Powered longitudinal and cross feeds
- Adjustable 4 position length-stop mechanism for accurate repetitive operation
- Micro adjustable saddle stop
- Dual calibrated dials incorporating metric & imperial graduations
- Coolant system with flexible hose enabling operator to manipulate flow direction
- Oil sight glass for head stock and gearbox
- Low voltage halogen work light
- Lubrication pump on saddle oiling slides
- D1-8 camlock spindle for quick chuck removal
- 12 spindle speeds from 25-1600rpm
- Large 80mm spindle bore

Product Brochure For L626

- 7.5kW / 10HP 415V main motor

Includes

- Taper Turning Attachment
- 315mm 3-jaw chuck with reverse jaws
- 350mm 4-jaw chuck
- Faceplate
- Fixed Steady with roller bearings
- Travelling steady with roller bearings
- Dead centres
- Thread chasing dial
- Foot brake
- Coolant system
- Work light
- Rear splash guard
- Spindle reducing bush

Recommended Accessories

L453

Lathe Turning Tool Kit - 3 piece
 Insert Type



L459

Lathe Threading Tool Kit - Insert
 Type



L296

Quick Change Toolpost



L296A

Quick Change Toolpost Holder -
 Std



D1272

Metric 135° Precision HSS Drill
 Set - 25 Piece



D1282

Imperial 135° Precision HSS
 Drill Set - 29 Piece



D126

Metric 135° Precision HSS Drill
 Set - 170 Pieces



C294

Industrial Drill Chuck - Keyless
 Type



Product Brochure For L626

D454A
4MT x JT3 Drill Chuck Arbor



D119
Metric 2MT HSS Drill Set



D424
Drill Sleeve - Morse Taper



D422
Drill Sleeve - Morse Taper




D425
Drill Sleeve - Morse Taper



M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



S090A
Soluble Metal Cutting Fluid - 1 Litre



S090
Soluble Metal Cutting Fluid - 5 Litre



S076
Cutting Tool Lubricant Fluid - 500ml



S077
Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075
Cutting Tool Lubricant Paste - 200g



Product Brochure For L626

S074

Cutting Tool Lubricant Paste -
500g



O000

SpillFix Universal Organic
Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant &
Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive

