

Product Brochure For L7081

CNC Turning Centre - LYNX 2600Y

Doosan Fanuc I Series (OiPlus) CNC Controller

Please Call



ORDER CODE:	L7081
MODEL:	LYNX 2600Y
Swing (mm):	630
Max Turning Diameter (mm):	380
Turning Length (mm):	610
Chuck Diameter (mm):	225
Bar Diameter Capacity (mm):	81
Tool Stations (No.):	12/24
Spindle Speed (rpm):	3500
Spindle Motor (kW):	18.5
Guideways:	LMG
Control:	Doosan Fanuc I Series (Oi-Plus)
Programming:	EZI Guide I Conversational
C Axes Resolution (deg):	0.001
Milling Speed (rpm):	5000
Milling Collets:	ER25
Sub Chuck Diameter (mm):	~
Y Axis Travel (mm):	105 (±52.5)



Description

Basic Specifications

630mm Swing Over Bed
 460mm Swing Over Saddle
 610mm Turning Length
 380mm Turning Ø
 105mm (±52.5mm) Y Axis Travel
 360deg (0.001deg Resolution) C Axis
 260kg Main Spindle Capacity, 520kg Shaft Work Capacity

Features


- Main Spindle
 - 81mm Bar Capacity
 - 250mm Ø Hydraulic Chuck
 - 3500RPM Spindle Speed
 - 18.5kW Spindle Power
 - 403Nm Spindle Torque
- Tailstock
 - 700mm Travel
 - Hydraulic Programmable Positioning
- Turret
 - BMT 55 Tool Mounting
 - 5000RPM Live Tool Speed
 - 5.5kW Live Tool Power
 - 42Nm Live Tool Torque
 - 24 Position / 12 Station Turret
 - 25mm Square / 40mm Ø Tool Capacity
 - ER25 Live Tool Collet Size
 - Eppinger PreciFlex Tooling System
- CNC Control
 - Doosan Fanuc I Series (OiPlus) CNC Controller

Product Brochure For L7081

- 15" Colour LCD Monitor
- Rigidsynchronised tapping
- Custom Macro B
- Ethernet Interface
- RS232 Interface
- USB & PCMCIA Memory Card Slot
- Doosan Ezi Guide "I" Conversational software:
- Graphical Turning Cycles
- Graphical Milling Cycles
- Full 3D Graphical Simulation
- Onboard G & M code assistance
- + more
- Standard Equipment Included
- 3 Jaw Hydraulic Power Chuck
- Grease Cartridge Auto Lubrication System
- Chuck Cleaning Air Blast
- Eppinger rotary tool holders with PreciFlex adapter set
- Coolant supply equipment
- Foot switches
- Transformer
- Full enclosure chip and coolant shield with front door interlock
- Hand tool kit
- Automatic lubrication equipment
- Comprehensive manuals incorporating, Operation, Maintenance, Programming, Spare Parts Diagrams, Hydraulic Schematics, Electrical Schematics and Ladder Diagrams.
- Safety name plates / tags where required
- Risk assessment
- Work light


Includes

- Standard Turret Tool Holder Package Included
- 4 x OD Tool Holder
- 3 x ID Tool Holder
- 1 x Face Tool Holder
- 1 x U Drill Cap
- 2 x Straight Milling Unit
- 2 x Angular Milling Unit
- 1 x Boring Sleeve Kit
- 1 x U Drill Sleeve Kit
- 1 x PreciFlex Adapter Kit
- 1 x ER 25 Milling Collet Set
- 1 x Hard & Soft Jaws
- Local Service and Support
- Commissioning & Testing Included
- Comprehensive Operator Training Included
- Hare and Forbes In House Service And Applications Staff
- Ongoing Support For Life Of The Machine
- Optional Equipment Included
- Chuck open close confirmation proximity switches
- Chip Conveyor (Side Discharge, Hinged Belt)
- Auto Tool Setter (Hydraulically operated)
- 7 Bar High Pressure Coolant
- Barfeed Interface
- Programmable Tailstock
- Chuck Cleaning Air Blast
- Auto Power Off Function
- Doosan Machine Tools changes its name to DN Solutions
- Read more at:



Product Brochure For L7081

Specific Features



Controls



LYNX 2600Y Inside



LYNX 2600Y Insert



Front