

Product Brochure For M639D

Heavy Duty Universal Milling Machine - BM-1600

Table Travel: (X) - 1200mm (Y) - 700mm (Z) - 500mm

Includes Digital Readout System & Servo Driven Ballscrew System X, Y & Z-Axis



ORDER CODE:	M639D
MODEL:	BM-1600
Digital Readout:	3-Axis Digital Readout
Type:	Universal Head
Table Size (mm):	1600 x 500
Column Type:	Dovetail
Spindle Taper - Vertical:	NT50
Spindle Taper - Horizontal:	NT50
Longitudinal Travel (X-Axis) (mm):	1200
Cross Travel (Y-Axis) (mm):	700
Vertical Travel (Z-Axis) (mm):	500
Type of Slides:	Dovetail (X), Square (Y & Z)
Ram Travel (mm):	45 - 745
Spindle to Table (mm):	50 - 550
Spindle to Base:	~
Spindle Travel / Diameter (mm):	~
Throat Depth (max.) (mm):	~
Tilting Head (Left ~ Right):	360°
Tilting Head (Forward ~ Back):	Fixed
Drilling Capacity (mm):	~
End Milling Capacity (mm):	~
Face Milling Capacity (mm):	~
Power Feed - Quill (mm/rev):	~
Power Feed - Longitudinal (X-Axis) (mm/min):	10 - 1000
Power Feed - Cross (Y-Axis) (mm/min):	10 - 1000
Power Feed - Vertical (Z-Axis) (mm/min):	5 - 500
Table T-Slot Size (inch / mm):	18
Work Table Load Capacity (kg):	1800
Spindle Speeds Vertical (No./ rpm):	~
Spindle Speeds Horizontal (No./ rpm):	~
Spindle Speeds - Universal Head:	27 (30 - 2050)
Motor Power - Vertical Spindle (kW / hp):	~
Motor Power - Horizontal Spindle (kW / hp):	~
Motor Power - Universal Head:	7.5 / 10
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	4500

Description

The BM-1600 universal milling machine features a solid, heavy cast iron construction, making this model ideal for heavy machining of oversize workpieces.

The servo-controlled feed system ensures constant torque when removing metal under extreme load. All this is combining with an extra-large hardened & ground working table with long travels to match.

Features

- 3-Axis digital readout fitted
 - Large 1600 x 500mm slotted work table
 - NT50 universal head swivels 360° & tilts vertical to horizontal position
 - Electric brake & rapid feed on X, Y & Z-Axis
 - Servo controlled feed motors on X, Y & Z-Axis ensures constant torque
 - Hardened ballscrew X, Y & Z-Axis preloaded for easy and precise feeds
 - Rigid, torsion-proof construction, dovetail guide X-Axis & wide square guides Y & Z-Axis
 - Robust transmission with hardened and ground gears & slide-ways
 - Hardened & ground work table & all X, Y & Z-Axis slideways
 - All slideways are automatically lubricated
- High grade casting for additional strength & minimal deformation

Product Brochure For M639D

- Quality electrics & overload protection in an easy access enclosure
- Table trays each end of work table
- Steel slide-way cover Y-Axis

Includes

- Safety cutter guard
- Coolant system
- Automatic oil lubrication system
- Cast iron table extensions
- LED light
- Base swarf tray
- M24 drawbar

Specific Features



Control Panel



Adjustable Control Arm




7.5kW / 10hp Spindle Motor



27 Geared Spindle Speeds



NT50 Spindle Taper




Universal Head - Tilts Vertical To Horizontal



1600 x 500mm Slotted Work Table



Automatic Slideway Lubrication System




Motor Power Toggle Switch



Horizontal Table Locks



Vertical Table Lock



27 Spindle Speed Chart

Product Brochure For M639D



Side Table Tool Rest



LED Work Light



Adjustable Table Travel Limit Stops



ON-OFF Isolation Switch