Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For P136P

Industrial Motorised Hydraulic Press Bender - 100 Tonne - AP-1020/100

10hp 415V Motor & 300mm Ram Stroke
Includes Multi Vee Pressbrake Attachment, Pressure Gauge & Foot Pedal Control

Ex GST	Inc GST
$27,500.00	$30,250.00



ORDER CODE:	P136P
MODEL:	AP-1020/100 - Pressbrake
Pressing Capacity (Tonne):	100
Hydraulic Ram Operation (Type):	Motorised System
Sliding Ram (left-right) (Yes / No):	No
Width Between Front Posts (mm):	1020
Width Between Side Posts (mm):	~
Table Top Opening - (Front to Back) (mm):	~
Ram To Table (Max.) (mm):	~
Cylinder Stroke (mm):	300
Ram Diameter (mm):	Ø220
Piston Diameter (mm):	~
Minimum Air Flow Rate required (L/Min):	~
Motor Power (kW / hp):	7.5 / 10
Voltage (V):	415
Floor Space (W x D x H) (mm):	2100 x 1050 x 2220
Nett Weight (kg):	1900

Description

100 tonne Hydraulic Press Bender Includes a Pressbrake Attachment

Note: Pressbrake attachment can be removed to use as a standard shop press

Features

- 1020mm x 86° offset top punch tool
- 1020mm x 95mm square bottom multi-vee die block, 10, 20, 30, 40 & 65mm vee
- 8mm maximum plate bending thickness with pressbrake attachment
- 1020 x 500mm die table with a Ø100mm centre hole
- 680mm distance between tables
- Fast approach slow bend
- Adjustment system for taking down or up the table
- Pressure adjustment
- Adjustable stroke
- T-slotted bottom table
- High capacity workshop forming press with extra 2 guide pistons in both sides
- Heavy duty steel welded frame
- Hydraulic operated pressing ram
- Pressure gauge fitted
- Safety overload valve
- Built to CE regulations
- Foot Pedal control
- Safety contactor switch with overload protection
- 8mm/sec Fast Approach
- 5mm/sec Working Speed
- 10mm/sec Return Speed

- Pre-Commissioning:
- 1. Press is run & tested prior delivery
- 2. Hydraulic oil is included with machine

Includes

Complete with Pressbrake Attachment

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For P136P

•

Specific Features


T Slotted Bottom Table


Multi vee Die Block


Adjustable Travel Limit Control



Pressure Gauge


Controls


Pressbrake Attachment Locks



2 x Guide Pistons


Foot Pedal Control



Heavy Duty Steel Welded Frame


Adjustable Table Height

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Recommended Accessories

O002

Superdraulic ISO 46 Hi Temp Hydraulic Oil



O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

