

Product Brochure For P138M

Industrial Motorised Hydraulic Press with Movable Head - 150 Tonne - DPM-K 1570-150

300mm Ram Stroke & 800mm Height From Ram To Table

Includes Movable Cylinder Ram, Pressure Gauge & Bending Vee Blocks



Ex GST **Inc GST**
\$21,500.00 **\$23,650.00**

ORDER CODE:	P138M
MODEL:	DPM-K1570
Pressing Capacity (Tonne):	150
Hydraulic Ram Operation (Type):	Motorised System
Sliding Ram (left-right) (Yes / No):	Yes
Width Between Front Posts (mm):	1570
Width Between Side Posts (mm):	360
Table Top Opening - (Front to Back) (mm):	425
Ram To Table (Max.) (mm):	800
Cylinder Stroke (mm):	300
Ram Diameter (mm):	Ø280
Piston Diameter (mm):	~
Minimum Air Flow Rate required (L/Min):	~
Motor Power (kW / hp):	11 / 15
Voltage (V):	415
Floor Space (W x D x H) (mm):	2660 x 1050 x 2480
Nett Weight (kg):	2100

LFSS
ŞAHİN MAKİNA



Description

The LFSS DPM-K1570 150 Tonne electric hydraulic press features a sliding cylinder which can be moved from side to side allowing for those offset pressing jobs. Suited for the Industrial workshop, for pressing of bearings, bushings & straightening shafts, bending steel as well as all general pressing applications.

Features

- Heavy duty steel welded frame
- Movable cylinder ram (left-right) allows operator to reposition the cylinder for off centre work
- 1570mm width between front posts
- Dual-speed joystick control (fast approach, slow bend)
- Pressure gauge fitted for easy control of pressing operations
- Heavy duty worktable with 5 adjustable positions
- Worktable can be adjusted using the provided chain system which works in conjunction with the hydraulic ram
- Safety overload valve
- Safety contactor switch with overload protection
- Built to CE regulations

Includes

- Pair bending plates
- Table lifting and lowering chains
- Hydraulic oil

Product Brochure For P138M

Recommended Accessories

P030

Bush Driver Set - 17 piece




P031

Bearing Race & Seal Driver Set - 10 piece



P1401

Steel Press Pin Driver Set - 11 piece



P455

Pressbrake Attachment - Suits Hydraulic Presses



O002

Superdraulic ISO 46 Hi Temp Hydraulic Oil



O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

