

Product Brochure For P143

Workshop Hydraulic Press - 20 Tonne - PP-20

Includes Adjustable Sliding Cylinder Ram



ORDER CODE:	P143
MODEL:	PP-20
Pressing Capacity (Tonne):	20
Hydraulic Ram Operation (Type):	Manual Hand Lever
Sliding Ram (left-right) (Yes / No):	Yes
Width Between Front Posts (mm):	550
Width Between Side Posts (mm):	~
Table Top Opening - (Front to Back) (mm):	94
Ram To Table (Max.) (mm):	950
Cylinder Stroke (mm):	140
Ram Diameter (mm):	Ø48
Piston Diameter (mm):	~
Minimum Air Flow Rate required (L/Min):	~
Motor Power (kW / hp):	~
Voltage (V):	~
Floor Space (W x D x H) (mm):	830 x 690 x 1720
Nett Weight (kg):	103



Description

The Hafco PP-20 20 tonne garage press has a variety of uses, ideal for removing and installing bushes, ball joints, bearings, gears, pulleys etc. The PP-20 also has the added feature of a sliding head simply loosen the clamping plate bolts and the head of the press can be moved to the side allowing for those offset pressing jobs.

The 20 tonne hydraulic ram and pump unit are also easily removed for use on other pressing jobs outside your workshop such as straightening or bending. The press is supplied with a pressure gauge, two heavy duty pressing plates and is constructed from industrial grade C channel making it ideal for mechanics or the serious home workshop.

Features

- Ideal for removing and installing - Bushing, Ball-joints, Bearings, Gears, Pulleys, etc
- High strength steel construction
- Adjustable sliding head up to 320mm travel between the vertical post
- H Frame style
- 20 tonne hydraulic ram and hand pump, easily removed for use on other pressing jobs
- 100mm pressure gauge

Includes

- Complete with bending plates

Product Brochure For P143

Specific Features



320mm Travel between Ram Centre



Ram Slide to the Left



Ram Slide to the Right

Recommended Accessories

P030

Bush Driver Set - 17 piece



P031

Bearing Race & Seal Driver Set - 10 piece



P1401

Steel Press Pin Driver Set - 11 piece



P450

Pressbrake Attachment - Suits Hydraulic Presses



O002

Superdraulic ISO 46 Hi Temp Hydraulic Oil



O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

