

Product Brochure For P178

Hydraulic Punch & Shear - 165 Tonne - IW-165SD

Dual Hydraulic Cylinders with Independent Operating Stations & Deep
 Hydraulic Punching Station



ORDER CODE:	P178
MODEL:	IW-165SD
Punching Pressure (Tonne):	165
Punching Table Type:	Manual with Guides and Adjustable Stops
Punching (Diameter x Thickness) - MS (mm):	Ø37 x 32, Ø50 x 24
Punching Throat Depth (mm):	510
Punching Maximum Stroke Length (mm):	100
Punching Cycles (15mm Stroke) - MS (cpm):	29
Punching Work Table Height (mm):	1050
Flat Bar Shear (W x Thickness) - MS (mm):	760 x 20, 400 x 30
Flat Bar Shear - Blade Length - MS (mm):	770
Flat Bar Shear Work Table Height (mm):	920
Angle Shear 90° - MS (mm):	205 x 205 x 20
Angle Shear 45° - MS (mm):	80 x 80 x 10
Angle Flange Trim (mm):	120
Angle Shear Work Table Height (mm):	1185
Round Solid Bar Shear - MS (mm):	Ø60
Square Solid Bar Shear - MS (mm):	60 x 60
Solid Bar Shear Work Table Height (mm):	1370
Notching - Rectangle - MS (mm):	63.5 x 90 x 16
Notching Work Table Height (mm):	920
Multi Vee Die Block (mm):	~
Vee Opening Sizes (mm):	~
Max. Tonne Capacity (T):	~
Bending Work Table Height (mm):	~
Motor Power (kW / hp):	15 / 20
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	5250

Description

The Sunrise Punch & Shears are manufactured in Taiwan, also known as Ironworkers are well recognised in our Australian market for the machines being reliable & durable due to their structurally well manufactured unique design & engineering excellence. Sunrise is ISO-9001 certified by BVQI, and our products meet the CE safety requirements and regulations. Sunrise relentlessly seeks continuous improvement and product development to keep a step ahead of their competitors.

The double cylinder "S/SD" series have two control foot pedals, & separate operations can be safely performed simultaneously without interference. The low pressure setting for tool change provides maximum operation safety. The long punching cylinder stroke & deep throat enable mounting a wide range of special optional equipment. The large punching base with the "T-slot" fixing provide a solid base for securing the punching tooling, as well as a wide range of optional & custom designed tooling.

The hydraulic system & components that drives the shearing beam & punching head is considerably very quiet compared to most other machines and operates efficiently smooth in all modes. The electrical components & DC control circuit are operated at a low 24 volt system & provides full protection & safety with in the separate key locked cabinet.

The Sunrise machines have proven themselves over & over again to provide trouble free service for many years in production and we have references all around Australia to verify our statement.

Features

- Five work stations, Punching, Notching, Plate Shearing, Angle Iron Shearing and Bar Shearing (all stations are guarded)
- Dual hydraulic cylinders allows simultaneous operation without interference
- Punching capacity up to 50mm standard
- Mitre cutting of angle iron
- Magnetic base halogen lamp
- Hydraulic system is protected with replaceable filter cartridge
- Adjustable stroke for faster punching
- Curved shear blade for minimal job distortion

Product Brochure For P178

- Most cutting blades are four-sided for long life
- Punch, shear & notching table fitted with stops & guides as standard
- Two-pedal operation allows two people to work machine to greatly speed up production
- Large punch table with multi-purpose bolster, featuring a removable block for channel and beam flange punching
- Adjustable length stop with one-touch electronic backgauge for greater efficiency in repetitious work
- PUNCHING
- Large hole punching up to Ø50mm as standard
- Overhang bolster for punching channel & beam flanges
- Large ruled support table with removable front section for leg down punching in angle or section
- Easily adjustable stripper & safety guard
- Pre-Commissioning:
 1. Punch & Shear is run & tested prior delivery
 2. Hydraulic oil is included with machine

Includes

- Full safety guarding at all workstations
- Tooling to all workstations
- Punch, Shear & Notch support tables
- Now with Quick Change Tooling
- 1 metre adjustable "Auto touch length stop" once the material has pushed the micro-switch stop the hydraulic system is activated to shear work piece

Optional Accessories

- Punch & dies are available in Round, Square, Rectangle & Oblong shapes

Specific Features



Machine Capabilities



Includes large hole punching up to 50mm Diameter



Includes Length Stop



Optional Single Vee Pressbrake Attachment



Optional Multi Vee Pressbrake



Optional Vee Notcher Punch Side



Optional Channel Shear



Optional Pipe Notcher

Product Brochure For P178



Optional Channel Punching Die Holder




Optional Goose Neck Die Holder



Optional Large Hole Punching



Optional Angle Bending Press



Optional Duplicating Table



Optional Multi Stop Gauge



Flat Bar Shear



Square Bar Shear



Round Bar Shear



Angle Shear



Angle Shear



Angle Shear



Angle Shear



Angle Shear




Work Light

Product Brochure For P178

Recommended Accessories

P163
Laser Guide System



P188
Single-Vee Pressbrake Bending Attachment



P188A
Single-Vee Pressbrake Bending Attachment



P187
Multi-Vee Pressbrake Bending Attachment



P165
Ø6-26mm Round Punch & Dies Set



P166
Ø11-40mm Round Punch & Dies Set



P726
Ø26mm Round Punch - RPN1



P726A
Ø26.7mm Round Die - RDN1



Product Brochure For P178

P6005
 8 x 20mm Slotted Punch



P6006
 8.7 x 20.7mm Slotted Die



P6001
 8 x 8mm Square Punch




P6002
 8.7 x 8.7mm Square Die



M800
 Rubber Mat - Anti-Fatigue



M805
 Rubber Mat - Anti-Fatigue



O000
 SpillFix Universal Organic Absorbent



O043
 Rust & Corrosion Preventive



O042
 General Purpose Lubricant & Corrosion Inhibitor



O040
 Rust & Corrosion Preventive



O044
 Rust & Corrosion Preventive



O004
 Superhydraulic ISO 46 Hi Temp Hydraulic Oil

