

Product Brochure For S120

Semi-Automatic Ferrous Cutting Cold Saw - SA350

135 x 85mm Rectangle Capacity

Ø350mm Blade, Pneumatic Vice Clamp, Variable Blade Speed

20~100rpm



Ex GST	Inc GST
\$16,000.00	\$17,600.00

ORDER CODE:	S120
MODEL:	SA350
Cutting Head Action:	Semi-Automatic
Operation Type:	Swivel - Dual Mitre
Round Capacity @ 90° / 45° (mm):	115 / 110
Square Capacity @ 90° / 45° (mm):	110 / 85
Rectangle Capacity @ 90° / 45° (WxH) (mm):	135 x 85 / 95 x 75
Blade Size - Diametre. x Bore (Ø) (mm):	350 x 40
Vice Clamping Fixture:	Pneumatic Vice
Coolant System:	Yes
Table Working Height (with Stand) (mm):	968
Blade Speed (rpm):	Variable 20~100
Motor Power (kW / hp):	2.2 / 3
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	280



Description

Features a smart, computerised actuation motor that alleviates the repetitious cutting process without compromising cutting capabilities and features of the ferrous saw range. With the ability to adjust the speed of the saw blade, this machine is ideal for working with a variety of materials at varying levels of thickness. This allows for clean, precise cuts without the risk of burning or overheating the material, variable speed reduces blade wear, extending the life of the saw blade.

Features

- 20 – 100 RPM Variable Speed
- Mitring locking device stops at 45° left, straight 90°, and 45° right
- Fully integrated coolant system provided on all machines
- Spindle and drive unit immersed in oil solution and enclosed within gearbox housing for smooth performance and reduced machine wear
- Every unit is provided with a high speed steel blade for general purpose cutting of ferrous solid and tube profiles
- Industrial lead-screw unit incorporated with a smart actuation motor which automates the cutting cycle for the operator
- Smart auto-detect of the cut piece size resulting in shortest stroke possible & fast cut times
- Auto feed speed adjustment through sections of varying thicknesses resulting in minimum blade wear
- Saw overload detection with feed modulation and reverse for safer operation
- Air-pneumatic vice clamp accommodates for a range of metal profiles ferrous solids and tube sections
- Brobolube standard lubricator

Product Brochure For S120

Specific Features



Right View

Recommended Accessories

S092

BROBOLUBE Industrial
Gearbox Oil



S136A

HSS Cold Saw Blade



S136B

HSS Cold Saw Blade



S136C

HSS Cold Saw Blade



S136D

HSS Cold Saw Blade



S136E

HSS Cold Saw Blade



S136F

HSS Cold Saw Blade



S137

HSS + COBALT Cold Saw
Blade



Product Brochure For S120

S137A

HSS + COBALT Cold Saw
Blade



S137B

HSS + COBALT Cold Saw
Blade



S137C

HSS + COBALT Cold Saw
Blade



S137D

HSS + COBALT Cold Saw
Blade



S137E

HSS + COBALT Cold Saw
Blade



S090A

Soluble Metal Cutting Fluid - 1
Litre



S090

Soluble Metal Cutting Fluid - 5
Litre



S091

Soluble Metal Cutting Fluid - 20
Litre



L300

Magnetic Swarf Remover



M9991

Magnetic Floor Sweeper



L812

Roller Conveyor



L814

Roller Conveyor Stand



Product Brochure For S120

W343
Roller Stand



W343A
Roller Stand



W3434
Roller Stand



W3436
Roller Stand - V-Type



S093
Screw Retaining



S100
Vice



S094
Leadscrew Handle / Nut
Assembly



S096
Vice Nut - Brass Type



S095
Dowel Pin



S097
Love Joy Coupling



S097A
Insert Love Joy



S098A
Coolant Pump



Product Brochure For S120

S098B

Coolant Pump & Conversion Kit



S099A

Return Spring Conversion Kit



S099B

Return Spring



S098

ON/OFF SWITCH 240V




M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



O000

SpillFix Universal Organic Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive

