

Product Brochure For S2492

610mm Manual Panbrake - PB-610H

610 x 1.0mm Mild Steel Bending Capacity
 Removable Individual Bending Fingers

Ex GST
\$400.00

Inc GST
\$440.00



ORDER CODE:	S2492
MODEL:	PB-610H
Bending Capacity - Mild Steel (mm):	1
Material Length Capacity (mm):	610
Floor Space (L x W x H) (mm):	~
Nett Weight (kg):	49.5



Description

Our new bench mount panbrake now features upgraded features making this model even more versatile.

We have upgraded the bending pivot point to include greaseable self-aligning bearings for a smoother more accurate bends, we have designed the bending apron to now be adjustable in height allowing you to easily bend to different radii with simple adjustments. We have made this machine more robust by increasing the material in the body with the total nett weight of 47kg, this helps to minimise flex in the body during bending. The clamping bar can also be adjusted to suit your chosen material, you can adjust the clamping pressure as well as the clamping bar position to ensure you get the bend angle with the right radius.

If you are looking a small bench mount panbrake with extra features over the competition this machine is for you.

Features

- Greaseable self-aligning bearings on bending pivot point for smoother operation
- Heavy steel fabricated construction, 47kg nett weight
- Cam operated adjustment for the clamping bar to suit differing materials thicknesses
- Height adjustable bending apron for bend radius adjustment
- Adjustable clamping pressure to prevent distortion during bending
- Multiple finger widths 26, 51, 77, 203, 254mm for bending of pans or boxes
- Single handed clamping operation
- Bending angle range from 0 – 135°
- Mild steel capacity is rated on hot rolled material with 250MPA

Product Brochure For S2492

Specific Features



Low View



Rear View



Left View



Material Clamp Blade Lever



Clamp Finger Cam Adjustment Nut



Removeable Fingers For Pans or Boxes



Apron Crown Adjustment

Recommended Accessories

M977

Digital Bevel Box

