

## Product Brochure For S559

### Hydraulic Guillotine - KG-83H

2470 x 3mm



|                                            |         |
|--------------------------------------------|---------|
| ORDER CODE:                                | S559    |
| MODEL:                                     | KG-83H  |
| Shearing Capacity - Mild Steel (mm):       | 3       |
| Shearing Capacity - Stainless Steel (mm):  | ~       |
| Shearing Length (mm):                      | 2470    |
| NC Control (Type):                         | ~       |
| Backgauge (Type):                          | ~       |
| Backgauge Travel (mm):                     | 600     |
| Pneumatic Sheet Supports:                  | ~       |
| Quick Action Blade Clearance Adjustment:   | ~       |
| Strokes / min (SPM):                       | 15      |
| Blade Angle (deg):                         | 2°      |
| Throat Depth (mm):                         | ~       |
| Motor Power (kW / hp):                     | 2.2 / 3 |
| Voltage / Amperage (V / amp):              | 415     |
| Floor Space Requirements (L x W x H) (mm): | ~       |
| Nett Weight (kg):                          | 3000    |



#### Features

- 2470mm x 3.0mm cutting capacity
- 2.2 kW 415V Motor
- Integrated hydraulic system
- Australian made using quality components
- Shadow lighting
- Manual backgauge
- Rear guard included
- Mild steel capacity is rated on hot rolled material with 250MPA

## Product Brochure For S559

### Specific Features



Control Box



Foot Control



Rear Guard



Hydraulic Unit shown with guards off



Hydraulic Unit



The Under Carriage



Left Hydraulic Housing



Right Hydraulic Housing & Micro Switch

### Recommended Accessories

M800

Rubber Mat - Anti-Fatigue

M805


Rubber Mat - Anti-Fatigue

O000

SpillFix Universal Organic Absorbent

O043

Rust & Corrosion Preventive



## Product Brochure For S559

O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive



O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

