Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For S724

Lockseamer - OZ-16

0.9 - 1.6mm Mild Steel Capacity



ORDER CODE:	S724
MODEL:	OZ-16
Capacity - Mild Steel (mm):	0.9 - 1.6
Stations (No.):	7
Work Height Pittsburgh (mm):	1000
Work Height - Power Flanger (mm):	~
Motor Power (kW / hp):	2.2 / 3
Voltage / Amperage (V / amp):	415
Machine Dimensions (L x W x H) (mm):	1400 x 610 x 1060
Nett Weight (kg):	250

Features

- GENERAL FEATURES OF OZ-FORM-16
- Pittsburgh rolls are supplied as standard
- Extended shafts for optional rolls such as Double Seam and Right Angle Flange
- Positive lubrication to all moving parts through grease nipples and oil holes
- Reinforced steel plate stand provides rigidity which eliminates drumming
- Hardened material guides
- Forming speed 5m/min maximum
- Made in Australia
- Mild steel capacity is rated on hot rolled material with 250MPA

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For S724



OZ-16 Includes: Pittsburgh Rolls

	Rolls	Capacity	Material used	Size
	Pittsburgh Lock Rolls 8mm Pocket	0.9 - 1.6mm	32mm	8mm pocket

Optional Rolls to suit:

	Rolls	Capacity	Material used	Size
	Double Seam Rolls (Type S)	0.4 - 0.9mm OZ-20 0.9 - 1.6mm OZ-16	32mm	10mm seam
	Drive Cleat Rolls	0.4 - 0.9mm OZ-20 0.9 - 1.6mm OZ-16	32mm	28mm wide