

## Product Brochure For S762

### Motorised Plate Curving Rolls - PR-136

1300 x 6.5mm Mild Steel Capacity

Initial Pinch Design



|                                            |                   |
|--------------------------------------------|-------------------|
| ORDER CODE:                                | S762              |
| MODEL:                                     | PR-136            |
| Curving System Type:                       | Initial Pinch     |
| Curving Material Length (mm):              | 1300              |
| Curving Plate Thickness - Mild Steel (mm): | 6.5               |
| Minimum Rolling Diameter (mm):             | 170               |
| Roll Diameter (mm):                        | 150               |
| Motor Power (kW / hp):                     | 3 / 4             |
| Voltage / Amperage (V / amp):              | 415               |
| Dimensions (LxWxH) (mm):                   | 2300 x 800 x 1340 |
| Floor Space (L x W x H) (mm):              | ~                 |
| Nett Weight (kg):                          | 1190              |



#### Features

- Initial pinch rolls with pre-bending
- Two rolls powered by gearbox drive system
- Swing out top roller enables cylinder to be removed
- Safety wire interlock system with emergency shut-off
- Precision ground rolls with wiring grooves
- Includes a conical bending guide roller
- Mobile foot pedal control
- Mild steel capacity is rated on hot rolled material with 250MPA

## Product Brochure For S762

### Specific Features



Right View

Rear View



Side View



Roll Adjustment Handles



Curving Roller Height Adjustment



Swing Out Top Roller Handle



Swing Out Top Roller



Conical Bending Guide Roller



Wire Groove Rolls



Safety Wire Interlock System



Switches



Foot Control