

Product Brochure For S7968

MRM-S 2550x150 - Motorised Plate Curving Rolls

2550 x 4mm Mild Steel Capacity
 3 Roll Initial Pinch

Ex GST **Inc GST**
\$34,500.00 **\$37,950.00**



ORDER CODE:	S7968
MODEL:	MRM-S 2550x150
Curving System Type:	Initial Pinch
Curving Material Length (mm):	2550
Curving Plate Thickness - Mild Steel (mm):	4
Minimum Rolling Diameter (mm):	225
Roll Diameter (mm):	150
Motor Power (kW / hp):	2.2 / 3
Voltage / Amperage (V / amp):	415
Dimensions (LxWxH) (mm):	4250 x 650 x 1020
Floor Space (L x W x H) (mm):	-
Nett Weight (kg):	2150



Description

The Isitan MRM-S 2550x150 3 Roll Initial Pinch Plate Rolling machines have a heavy duty, steel welded frame construction for superior rigidity and are used for applications up to a maximum material thickness of 4mm mild steel. The asymmetric design provides pre-bending capability on the machine and the swing out top roll allows for removal of complete cylindrical components. Other models ranging up to 3050mm working length are available.

Features

- SAE 150 quality certified steel rolls with high tensile strength
- Induction hardened rolls suitable for stainless steel
- Steel welded main frame
- Conical bending device
- Digital readout display for rear roll position
- Motorised up & down on rear roll
- Manual pinching of bottom roll
- Manual handwheel adjustment of the pre-bending roll
- Swing out top roll for removal of complete cylinders
- Central lubrication system
- Safety cut out trip wire
- Brake motor standard for precision bending
- Mobile control panel
- Mild steel capacity is rated on hot rolled material with 250MPA