

Product Brochure For S828

Cold Saw, Includes Stand - CS-315D

110 x 70mm Rectangle Capacity
 Ø315mm Blade, Dual Speed 22 / 44rpm



Ex GST
\$3,290.00

Inc GST
\$3,619.00

ORDER CODE:	S828
MODEL:	CS-315D
Cutting Head Action:	Manual
Operation Type:	Swivel - Dual Mitre
Round Capacity @ 90° / 45° (mm):	100 / 90
Square Capacity @ 90° / 45° (mm):	82 / 75
Rectangle Capacity @ 90° / 45° (WxH) (mm):	110 x 70 / 85 x 70
Blade Size - Diametre. x Bore (Ø) (mm):	315 x 32
Vice Clamping Fixture:	Manual
Coolant System:	Yes
Table Working Height (with Stand) (mm):	980
Blade Speed (rpm):	22 / 44
Motor Power (kW / hp):	1.5 / 2
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	175



Description

Manufactured in Taiwan

The Hafco MetalMaster manual cold saw consists of a 315mm circular saw blade that runs at a relatively slow speed in conjunction with a coolant system. These cold saws are designed to cut at 90°, or mitre up to 45° in either left or right side of the material simply by releasing the lever located at front of machine. Each machine comes standard with a very heavy and strong cast iron frame base with a cast dual pivot saw head supported by an industrial swivel base system, which makes a MetalMaster cold saw one of the most rugged machines on the market.

The MetalMaster manual cold saw head is well balanced and uses a long actuating handle giving the operator greater leverage and control to guide the saw blade through the work piece of tubing or pipe etc., with ease and utilises a quality head retraction system for returning the cold saw head to the start position. The vice clamps the work piece on both sides of a cut, which extends blade life because the cut off does not drop into the blade.

Features

- Rugged cast iron construction offers years of accurate cutting
- Lock at any angle between -45° or +45° mitre in both directions via locking lever
- Degree markings engraved onto swivelling base for quick and accurate mitre cutting
- Dual material clamp system providing burr free cuts on both pieces of material
- Quick action vice clamp lever designed to increase production
- Built in blade coolant pump system with flow control valve
- Oil sight glass located on right side of the gearbox so operator can maintain correct lubrication levels according to specifications provided
- Dead man trigger switch located on cutting handle provides operator safety on/off power control
- Automatic retract safety blade guard covers blade when returned to home position
- Spring assisted head return provides a even balance during cutting operation and reduces operator fatigue
- HSS cutting blade is included for general types of material and thickness

Includes

- Blade
- Stand
- Coolant system
- Material length stop

Product Brochure For S828

Specific Features




Control Panel



Adjustable Cut Length Stop



Swivel Head Degree Scale NEW



Swivel Head Lock Lever



Heavy Duty head Pivot Hinge



Adjustable Vice Jaws



Deadman Trigger Switch



Coolant Pump and Tank



Collant Flow Control Valve



Side View

Product Brochure For S828

Recommended Accessories

S092
 BROBOLUBE Industrial
 Gearbox Oil



S158
 HSS Cold Saw Blade



S158A
 HSS Cold Saw Blade



S158B
 HSS Cold Saw Blade



S158C
 HSS Cold Saw Blade



S158D
 HSS Cold Saw Blade



S158E
 HSS Cold Saw Blade



S158J
 HSS Cold Saw Blade



Product Brochure For S828

S158K
HSS Cold Saw Blade



S158M
HSS + COBALT Cold Saw Blade



S158P
HSS + COBALT Cold Saw Blade



S158S
HSS + COBALT Cold Saw Blade



S158X
HSS + COBALT Cold Saw Blade



S090A
Soluble Metal Cutting Fluid - 1 Litre



S090
Soluble Metal Cutting Fluid - 5 Litre



S076
Cutting Tool Lubricant Fluid - 500ml



S077
Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075
Cutting Tool Lubricant Paste - 200g



S074
Cutting Tool Lubricant Paste - 500g



S091
Soluble Metal Cutting Fluid - 20 Litre



Product Brochure For S828

L300
 Magnetic Swarf Remover



M9991
 Magnetic Floor Sweeper



L812
 Roller Conveyor



L814
 Roller Conveyor Stand



W343
 Roller Stand



W343A
 Roller Stand



W3434
 Roller Stand




W3436
 Roller Stand - V-Type



M800
 Rubber Mat - Anti-Fatigue



M805
 Rubber Mat - Anti-Fatigue



O000
 SpillFix Universal Organic Absorbent



O043
 Rust & Corrosion Preventive



Product Brochure For S828

O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive



S812

Coolant Pump

