

Product Brochure For S881

Hydraulic NC Pressbrake - APH-3106

120T x 3100mm, ESA EC4 CNC Control

Includes Laser Guarding System



ORDER CODE:	S881
MODEL:	APH-3106
Control Unit (Type):	EC4 CNC
Nominal Pressure - Tonnage (Ton):	120
Nominal Pressure - Kilonewtons (kN):	1200
Length of Work Table (mm):	3100
Distance Between Columns (mm):	2550
Throat Depth (mm):	410
Maximum Open Height (mm):	485
Ram Stroke (mm):	210
Machine Axis (No.):	2
Safety Guarding System (Type):	Laser Guarding System
Backgauge Travel (mm):	650
Table Bed Crowning System (Type):	-
Motor Power (kW / hp):	11/ 15
Motor Voltage (V):	415
Floor Space Requirements (L x W x H) (mm):	-
Nett Weight (kg):	8100



Description

Also Available
 ALSO AVAILABLE WITH DELEM CONTROL
 1600 to 4100mm length capacity
 40T to 300T capacity. Please call for specifications and prices

Features

- Pre-set, 2 speed bending cycle for rapid approach, slow bending and rapid release
- Hydro-mechanical system assuring accurate parallelism and repeatability
- 2-axis Italian NC control and quick release tool holders
- 750mm power backgauge with hardened ballscrews
- Digital stroke position display with electronic depth stop positioner
- Top tool holder system with wedge adjustment
- Hydraulic overload protection
- Includes: Laser safe light guarding
- Mild steel capacity is rated on hot rolled material with 250MPA

Product Brochure For S881

Specific Features



Controller

Recommended Accessories


M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



O000

SpillFix Universal Organic Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive



O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

