

## Product Brochure For S907GL

### Hydraulic NC Pressbrake - PB-135E

135T x 4000mm - Includes Laser Safety Guarding

Estun NC-E21 Control 2-Axis with Leadscrew Backgauge



|                                            |                    |
|--------------------------------------------|--------------------|
| ORDER CODE:                                | S907GL             |
| MODEL:                                     | PB-135E            |
| Control Unit (Type):                       | Estun NC-E21       |
| Nominal Pressure - Tonnage (Ton):          | 135                |
| Nominal Pressure - Kilonewtons (kN):       | 1250               |
| Length of Work Table (mm):                 | 4000               |
| Distance Between Columns (mm):             | 3200               |
| Throat Depth (mm):                         | 320                |
| Maximum Open Height (mm):                  | 400                |
| Ram Stroke (mm):                           | 125                |
| Machine Axis (No.):                        | 2                  |
| Safety Guarding System (Type):             | Laser System       |
| Backgauge Travel (mm):                     | 520                |
| Table Bed Crowning System (Type):          | -                  |
| Motor Power (kW / hp):                     | 7.5 / 10           |
| Motor Voltage (V):                         | 415                |
| Floor Space Requirements (L x W x H) (mm): | 4700 x 2000 x 2600 |
| Nett Weight (kg):                          | 8325               |



### Description

Metalmaster Press brakes are designed and tested to provide precision bending capabilities demanded in industry. The main structural frames are constructed from rolled, stress relieved solid steel to prevent distortion during the bending process and under extreme continuous loads.

Featuring a heavy duty adjustable torsion bar with a positive stop system ensures consistent and accurate bending.

All electrical components are of European quality supplied by leading brands such as Siemens, Schneider, Telemecanique, Merlin Gerin and ABB.

Note: Guarding systems are required on pressbrakes for OHS compliance.

### Features

- Hydraulic synchronised positive stop design, the ram stroke is controlled by a precision mechanical nut depth stop built into each cylinder, electronically controlled by Estun NC-E21 digital control assuring accuracy and repeatability.
- Mono-block steel frame design, welded, stress relieved and final machining ensures minimal bed deflection under load.
- Bending Parallelism is ensured by the oversize top beam and heavy duty torsion bar.
- Conveniently mounted control box on pendant for quick swivel and adjustments.
- Estun NC-E21 programmable digital control stores up to 40 unique programs with 25 automatic progressive bending steps in each individual program, assuring production accuracy & repeatability every time.
- Estun NC-E21 programmable leadscrew back gauge system, simply enter the desired measurement into the controller and press start, the back gauge then will move quickly into the position you have requested.
- Operator adjustable stroke open height & mute height switches enables increased productivity
- Adjustable bending pressure control allows the operator to quickly and accurately set the pressure required for different material. This user friendly system incorporates hydraulic overload protection.
- European style Intermediate top tool clamping system, featuring an adjustable wedge clamping system for crowning as well as a safety key to stop the punch dropping when changing punch positions.
- Segmented heavy duty 86° offset top punch is segmented for selective bend width applications and offset for return bend clearance.
- Multi vee ("V") bottom die is made from one 4000mm solid die block design to handle heavy plate, safety edge vee ("V") is incorporated in bottom die block.
- Sliding front material sheet supports enabling a wide range of material sizes to be aligned and supported at the required height. This feature is achieved with a "T" slot machined down the total length of the die bed; sheet supports are also adjustable vertically to assist in supporting material with return bends already folded.
- Rear sliding safety gate with micro switch combined with access panels placed at each end of machine allows the operator to clearly view tooling and work piece during the bending operation, Metalmaster specially design gates to suit Australian safety requirements
- The vertical top beam slides are treated to provide greater wear resistance and increased accuracy.

## Product Brochure For S907GL

- Mild steel capacity is rated on hot rolled material with 250MPA

- Pre-Commissioning:
  - Press brake is run & tested prior delivery
  - Hydraulic oil is included with machine

### Includes

- ESTUN NC- E21 control mounted on a swivel pendant for optimal ergonomics
- Adjustable front sheet support arms
- Emergency stop buttons strategically located on control panel and foot control
- Mobile dual operation foot control
- Segmented 86° offset top punch tooling
- Solid one piece four way multi vee (V) die block
- Top tooling tool intermediate holder system with wedge type adjustment
- Powered leadscrew back gauge with 520mm travel, operated by Estun NC-E21 control
- Oil tank level indicator
- Metal constructed safety guarding
- Integrated hydraulic system allowing rapid approach speed switching automatically to slow bend

### Specific Features



Enclosed Rear Safety Guarding



Laser Mount Left



Laser Mount Right



Laser Alignment Guide



NC Estun E21 Controller



NC Estun E21



Mobile Foot Control



Adjustable Sliding Front Sheet Supports



Intermediate Clamps



Adjustable Top Tool Taper Wedge System



Laser Face Left



Laser Face Right

Product Brochure For S907GL



Adjustable Pressure Control



Tooling Bed Clamps




Estun NC E21 Control Ballscrew Backgauge




Backgauge Stops




Synchronised Torsion Bar




Segmented Top Punch



One Piece 4 Sided Die



Tonnage Calculation Chart



Lubrication Chart

## Product Brochure For S907GL

### Recommended Accessories

#### S988

Quick Action Intermediate  
Clamps



#### S991

86° Top Punch Pressbrake  
Tooling




#### S991S

86° Top Punch Pressbrake  
Tooling - Segmented



#### S993

95mm Die Block Pressbrake  
Tooling




#### S9920

86° Top Punch Gooseneck  
Pressbrake Tooling



#### S9920S

86° Top Punch Gooseneck  
Pressbrake Tooling -  
Segmented



#### S990

35° Top Punch Pressbrake  
Tooling



#### S990S

35° Top Punch Pressbrake  
Tooling - Segmented



## Product Brochure For S907GL


### S996

15° Top Punch Pressbrake Tooling



### S996A

60mm Die Block Pressbrake Tooling




### S996B

60mm Die Rail Pressbrake Tooling



### Q200

Combination Set



### Q200A

Combination Set



### Q201

Universal Bevel Protractor




### M800

Rubber Mat - Anti-Fatigue



### M805

Rubber Mat - Anti-Fatigue



### O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

