

Product Brochure For S924A

Mechanical Guillotine - MG-440

1300 x 4mm Mild Steel Shearing Capacity

Manual Backgauge & Includes Rapid Blade Adjustment



Ex GST
\$7,750.00

Inc GST
\$8,525.00

ORDER CODE:	S924A
MODEL:	MG-440
Shearing Capacity - Mild Steel (mm):	4
Shearing Capacity - Stainless Steel (mm):	2.5
Shearing Length (mm):	1300
NC Control (Type):	~
Backgauge (Type):	Manual
Backgauge Travel (mm):	500
Pneumatic Sheet Supports:	~
Quick Action Blade Clearance Adjustment:	Yes
Strokes / min (SPM):	22
Blade Angle (deg):	2°
Throat Depth (mm):	~
Motor Power (kW / hp):	4 / 5.3
Voltage / Amperage (V / amp):	415
Floor Space Requirements (L x W x H) (mm):	2060 x 2030 x 1312
Nett Weight (kg):	1450

METALMASTER



Features

- 1300mm x 4mm cutting capacity
- 4kW / 5.3hp 415V brake motor
- Quick action blade clearance adjustment for shearing material 1 - 4mm
- Full length material clamp bar load spring assisted
- One shot lubrication pump & reservoir for slideway protection
- Manual backgauge with digital scale display unit
- Equipped with shadow line lighting-alignment device
- Roving foot pedal control
- Clamp beam design allows clear view to shadow line on material
- Blades made from 9CrSi material suitable for cutting stainless steel
- Transfer balls inserted into work table allowing larger sheets to be easily positioned to the cut position and squaring arm
- Front sheet supports with ball bearing guides preventing material damage when setting up
- Three safety photo electric light beams on rear guarding
- Safety reset rear guarding button mounted to back of electrical box
- Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
- 1. Guillotine is run & tested prior delivery

Product Brochure For S924A

Specific Features



Right View



Rear View



Control Panel



Quick Action Blade Clearance Adjustment



Squaring Arm with Measuring Scale



Front Sheet Supports



Material Transfer Balls on Table



Manual Backgauge with Digital Readout



Backgauge Digital Readout



3 Safety Electro Photo Sensors



One Shot Lubrication




Roving Foot Pedal with Emergency Stop

Product Brochure For S924A

Recommended Accessories

S9981

1320mm Sheet Metal Guillotine
 Blade Set - 9CrSi




M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



O000

SpillFix Universal Organic
 Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant &
 Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive



Product Brochure For S924A

O004

Superdraulic ISO 46 Hi Temp
Hydraulic Oil

