

Product Brochure For W08046

BuildPro Ball Lock Bolt - Flush Mount - T65025

For connecting Accessory to Tabletop - 28mm Capacity
 Suits Ø16mm Welding Tables Holes



ORDER CODE:	W08046
MODEL:	T65025
Type:	Flush Mount Ball Lock Bolt
Suits Table Size (Ø):	16mm
Clamping Capacity:	28mm
Size:	-
Quantity Per Pack (No.):	1
Over all Length:	
Nett Weight (kg):	0.05

BuildPro™



Description

An essential component in Modular Fixturing!

Ball Lock Bolts are a time-saving, efficient, and handy method of fastening fixture elements to the BuildPro®; Tabletop, especially in tight spaces, and hard-to-reach areas of the tabletop. The quick-setting Ball Lock Bolts provide accurate locating and clamping at the same time.

Insert the Ball Lock Bolt over the fixturing element to be mounted on the tabletop. Turn the knurled head with your hands, for initial positioning. The Ball Lock Bolt system consists of three locking steel balls in the bolt shank that move outward to lock against the bottom chamfer of the table plate, pulling the fixture components securely downward and tightening them in place.

Once all the Bolts are positioned as required, tighten the socket head screw top of the bolts with a hex wrench. Ball Lock Bolts also release quickly, from the Bolt top, with a turn of your hex wrench. The automatic, and quick-locking feature of the Ball Lock Bolts translates into savings in time and effort.

- Ball Lock Bolts are an essential component in modular fixturing.
- When engaged (tightened) three steel locking balls move outward to lock underneath the table, securely attaching fixturing elements to the table with downward pressure.
- Use Ball Lock Bolts to fasten elements to the tabletop, or to Economy Clamping Squares, or Right Angle Brackets.

The very practical, modular design of the BuildPro®; Table makes it easy to set-up and tear down for job at hand, big or small. Save time and money by holding, positioning and locating quickly and easily with a wide variety of BuildPro®; clamps and accessories.

All BuildPro®; Tables have 16mm thick steel plate with 16mm holes in a 50mm grid pattern. All tables, except BuildPro®; MAX, have 40mm slots between plates.

Features

- Flush Mount
- For connecting an accessory to the tabletop, 28mm capacity
- 4mm Hex Wrench Size

Includes

- 1 x T65025 Ball Lock Bolt

Product Brochure For W08046

Specific Features



Ball Lock Bolts are an essential component in modular fixturing



When engaged tightened three steel locking balls move outward to lock underneath the table



Use Ball Lock Bolts to fasten elements to the tabletop or to economy clamping squares or right angle brackets



Efficient way of fastening fixture elements

Recommended Accessories

W08048

BuildPro Adjustable Ball Lock Bolt

