Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For W415

Thicknesser - HSS Blades - T-20

508 x 200mm (W x H) Material Capacity
Includes 4 x High Speed Steel Blades



ORDER CODE:	W415
MODEL:	T-20
Material Width Capacity (mm):	508
Material Height Capacity (mm):	200
Minimum Material Length (mm):	190
Maximum Depth of Cut (mm):	6mm @ 508mm wide
Cutter Type:	HSS Blades - Straight
Quantity of Cutters (No. x Type):	4 x Blades
Cutter Block Diameter (mm):	80
Cutter Block Speed (rpm):	5000
Quantity of Spirals (No.):	~
Length of Table (mm):	650
Length of Table with Extensions/Rollers (mm):	1470
Feed Speed (m/min):	4.8 / 6
Dust Outlet Diameter (mm):	125
Motor Power (kW / hp):	3.75 / 5
Plug Type (V / amp):	415
Floor Space (W x D x H) (mm):	1000 x 1470 x 1030
Floor Space With Option Stand (W x D x H) (mm):	~
Nett Weight (kg):	420

Description

The Hafco T-20 thicknesser manufactured in Taiwan with four knife cutter head is a heavy duty machine with very substantial cast iron body and heavy gauge sheet steel base. The cast iron thicknessing table which has a polished surface to help timber slide freely as well as to help reduced vibration to improved quality of cut.

The cutter head is supported by 4 x solid pillars at each corner and the steel drive rollers have ribbing to ensure positive grip on the timber through the machine via two speed gearbox at a rate of 16 or 20fpm. The feed roller pressure can be adjusted with the four adjusters on the top of the machine. The depth of cut is set by means of the cranked handle on the side using the setting scale positioned on the in-feed side or digital readout.

Power is provided by a 3750W / 5hp 415V induction motor, housed within the base and transmitting power to the cutter block via a twin pulley vee belt drive system.

Features

- Suits professional workshop
- Heavy cast iron machine
- 4 x HSS blades pre-set in cutter head with quick action blade change
- Cutting speed 5000 rpm
- 2 speed feed rollers with pressure adjustment
- 125mm dust chute
- Digital Height Gauge (Includes LR44 battery)
- Industrial contactor switch with overload protection
- Anti kick back fingers
- Table locking handles lock both left & right
- Heavy duty four post design with protective concertina covers
- Same model sold for over 20 years
- Quality Taiwanese Manufacture

Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For W415

Specific Features



2 Speed Feed Gearbox



Digital Height Readout



Magnetic Safety Switch



Robust 4 Post Design

Recommended Accessories

WL005
BLADE SET HSS PKT 4



W754
Spiral Cutter Head - Carbide Inserts



W331
Industrial Dust Collector



W931
Mobile Base - Heavy Duty



W344
Wood Dust Accessory Kit



W334
Dust Hose Reducer



W333
Dust Hose Reducer



W335
Blast Gate



Sydney: (02) 9890 9111
Brisbane: (07) 3715 2200
Melbourne: (03) 9212 4422
Perth: (08) 9373 9999
Adelaide: (08) 9373 9969
sales@machineryhouse.com.au
www.machineryhouse.com.au

Product Brochure For W415

W336
Dust Hose Elbow - 90 Degree



W337
Dust Hose Y Adaptor



W338
Dust Hose Universal Dust Hood



W339
Dust Hose Floor Sweeper Attachment



W340
Dust Hose Clamp



W341
Dust Hose Clamp

