

Product Brochure For XXLA238

Centre Lathe - CL-75

560 x 2000mm Turning Capacity - 105mm Spindle Bore
 Includes Digital Readout System, Quick Change Toolpost & Taper Turning Attachment

Limited Stock

Ex GST	Inc GST
\$6,359.09	\$6,995.00



ORDER CODE:	L626D
MODEL:	CL-75
Branch Location (State):	MELBOURNE
Type:	Lathe
Brand:	HAFCO
Capacity:	560 x 2000mm
Speed Range (rpm):	25 - 1600
Motor Power (kW / hp):	7.5 / 10
Voltage / Amperage (V / amp):	415



Description

PICK UP MELBOURNE ONLY
 NO WARRANTY
 USED MACHINE

Features

- 2 Axis digital readout system
- Quick change toolpost
- Taper turning attachment fitted to saddle
- Triple bearings supporting headstock spindle
- Adjustable taper roller bearings providing spindle accuracy
- Precision 'V'-beds & headstock gears are all hardened & ground
- One piece cast iron base increases rigidity
- Overload protection on drive motor and coolant system
- Universal enclosed gearbox incorporating metric & imperial thread capabilities
- Inching button incorporated on the control panel for convenient spindle speed selection
- Foot operated spindle brake with safety cut out switch
- 350mm wide induction hardened heavy duty cast iron bed
- Removable gap bed allowing work piece to swing up to 785mm
- Chuck guard fitted with safety micro switch
- Powered longitudinal and cross feeds
- Adjustable 4 position length-stop mechanism for accurate repetitive operation
- Micro adjustable saddle stop
- Dual calibrated dials incorporating metric & imperial graduations
- Coolant system with flexible hose enabling operator to manipulate flow direction
- Oil sight glass for head stock and gearbox
- Low voltage halogen work light
- Lubrication pump on saddle oiling slides
- D1-8 camlock spindle for quick chuck removal
- 12 spindle speeds from 25-1600rpm
- 105mm spindle bore
- 7.5kW / 10HP 415V main motor

Includes

- 2 Axis digital readout system

Product Brochure For XXLA238

- Quick change toolpost
- Taper turning attachment fitted to saddle
- Concertina leadscrew covers
- 315mm 3-jaw chuck with reverse jaws
- 350mm 4-jaw chuck
- Face plate
- Fixed steady with roller bearings
- Travelling steady with brass guides
- Dead centres
- Thread chasing dial
- Foot brake
- Coolant system
- Work light
- Rear splash guard
- Spindle reducing bush

Specific Features



Image 2



Image 3

Recommended Accessories

L296

Quick Change Toolpost

L048

Right Hand Turning Tool Holder

L049

Left Hand Turning Tool Holder

L041

Right Hand Turning Tool Holder



Product Brochure For XXLA238


L042
 Left Hand Turning Tool Holder



L453
 Lathe Turning Tool Kit - 3 piece Insert Type



L459
 Lathe Threading Tool Kit - Insert Type



L467
 Professional Lathe Parting Tool Kit - Insert Type



C047
 5MT Pipe Centre - 70° Cone



C290
 Heavy Duty Drill Chuck - Keyed Type



C294
 Industrial Drill Chuck - Keyless Type



D454A
 4MT x JT3 Drill Chuck Arbor



D425
 Drill Sleeve - Morse Taper



D424
 Drill Sleeve - Morse Taper



D422
 Drill Sleeve - Morse Taper



D1272
 Metric 135° Precision HSS Drill Set - 25 Piece



Product Brochure For XXLA238

D1282
 Imperial 135° Precision HSS
 Drill Set - 29 Piece



D126
 Metric 135° Precision HSS Drill
 Set - 170 Pieces



D119
 Metric 2MT HSS Drill Set



S090A
 Soluble Metal Cutting Fluid - 1
 Litre



S090
 Soluble Metal Cutting Fluid - 5
 Litre



S076
 Cutting Tool Lubricant Fluid -
 500ml



S077
 Drilling, Tapping & Cutting Tool
 Lubricant Spray - 400g



S075
 Cutting Tool Lubricant Paste -
 200g



S074
 Cutting Tool Lubricant Paste -
 500g



S091
 Soluble Metal Cutting Fluid - 20
 Litre



G664
 Lathe Leadscrew Cover Kit



L300
 Magnetic Swarf Remover



Product Brochure For XXLA238


M9991
 Magnetic Floor Sweeper



M800
 Rubber Mat - Anti-Fatigue



M805
 Rubber Mat - Anti-Fatigue



A358
 Sky Hook Lifting Device



A358A
 Chuck Hook



O000
 SpillFix Universal Organic Absorbent



O043
 Rust & Corrosion Preventive



O042
 General Purpose Lubricant & Corrosion Inhibitor



O040
 Rust & Corrosion Preventive



O044
 Rust & Corrosion Preventive

