

Product Brochure For XXSH244

Hydraulic NC Panbrake - Ezy Touch Screen Control - PB-860T

2500 x 6mm Mild Steel Bending Capacity



ORDER CODE:	XXSH244
MODEL:	PB-860T
Branch Location (State):	Sydney
Type:	PANBRAKE 2500X6MM
Brand:	Metalmaster
Capacity:	2500 x 6mm Mild Steel
Speed Range (rpm):	~
Motor Power (kW / hp):	7.5 / 10
Voltage / Amperage (V / amp):	415



Description

Used Equipment

The most recent edition to the Metalmaster Hydraulic NC Panbrake range now comes complete with a 7" colour touch screen control panel. The beauty of this Ezy-Touch screen design is it can store a massive 99 programs with 20 bend angles per program, and each bend angle allows you to fine-tune the material bend compensation. This feature simply removes the guess work out and takes bending to the next level to achieve accuracy & repeatability every time. Another unique attribute built-in is a quick action head allowing adjusting for the different material thickness from 1mm to 6mm

The welded frame is constructed from heavy gauge steel for superior strength & minimal flex when operating under full capacity with extreme load. Metalmaster have thought outside the box when designing & manufacturing this machine as they have also made the clamp fingers extra long so you can bend up deep boxes or pans.

Features


- 2500mm x 6mm bending capacity
 - Ezy-Touch NC Touch Screen Control features 99 programs, each program has up to 20 bends & each bend has material compensation. It also incorporates a quick bend function for jobbing work
 - Auto cycle: after clamping bottom beam will bend to pre-set angle and return, head unclamps to set position
 - Ezy-Touch NC programmable opening height & bending dwell timer ensures consistent bending angle
 - Quick action rapid head adjustment to optimise bend radius on 1-6mm material thickness
 - Heavy duty steel fabricated construction
 - Roving foot pedal incorporates control panel for maximum flexibility
 - High quality components ensure reliable performance for years of continuous operation
 - Extended fingers allows bending of pans or boxes to a depth of 205mm
 - Includes an adjustable rear manual backgauge, also adjustable for tapered material
 - Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
 1. Panbrake bender is run & tested prior delivery
 2. Hydraulic oil is included with machine

Product Brochure For XXSH244

Specific Features



1



2

Recommended Accessories

S581T

Hydraulic NC Panbrake - Ezy Touch Screen Control

S584T

Hydraulic NC Panbrake - Ezy Touch Screen Control

S585T

Hydraulic NC Panbrake - Ezy Touch Screen Control

M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue

O000


SpillFix Universal Organic Absorbent

O043

Rust & Corrosion Preventive

O042

General Purpose Lubricant & Corrosion Inhibitor



Product Brochure For XXSH244

O040
Rust & Corrosion Preventive



O044
Rust & Corrosion Preventive



O004
Superdraulic ISO 46 Hi Temp Hydraulic Oil

