

Product Brochure For Z41798

Mini Beveller Ring Type - AMB-0307

Bevels up to 7mm C mild steel, & 3mm C in stainless steel
 & Radius bevelling up to 4mm (R4)



ORDER CODE:	Z41798
Rated Air Pressure (psi):	6
Air Consumption (no Load) (CFM):	0.9
No Load Speed (rpm):	14,000
Chamfer Capacity - Mild Steel:	OC~7C, 2R, 3R, 4R
Chamfer Capacity - Stainless Steel:	OC~3C, 2R, 3R, 4R
Chamfer Angle (deg):	15 - 45
Weight (kg):	2.9



Description

Application to stainless steel and mild steel bevelling

Features

- Bevels up to 7mm C mild steel, 3mm C in stainless steel
- Radius bevelling up to 4mm (R4)
- Bevelling angle can be adjusted from 15 Deg. to 45 Deg.
- Simple to adjust bevelling depth
- Super solid inserts with 4-sided blade
- Pipe outer edge can also be processed with standard accessories

Includes

- 3mm & 4mm hex socket screw key : 1 x piece each
- 8mm x 25mm hex socket set screw for pipe bevelling minimum of 200mm diameter: 2 x pieces
- 4mm x 7mm insert set screw : 1 x piece
- Hex nut M8 : 2 x pieces

Optional Accessories

- TA9A896 : insert 12.7 with hole Ass'y : 10 piece set
- TB01159 : Insert 12.7 with hole Ass'y : 10 piece set
- TB01791 : Insert 12.7 Ass'y R2 : 10 piece set
- TB01651 : Insert 12.7 Ass'y R3 : 10 piece set
- TB01790 : Insert 12.7 Ass'y R4 : 10 piece set
- TB02539 : Attachment for small dia. pipe : 1 set (80mm to 200mm diameter)
- TQ01683 : Spanner T-15D : 1 x piece