

Product Brochure For ZS806

Motorised Plate Curving Rolls - PR-252A

Motorised Up/Down Rear Roll, DRO Control Panel & Initial Pinch

Design 2.5mm Mild Steel Capacity



ORDER CODE:	ZS806
MODEL:	PR-252A
Branch Location (State):	Sydney
Type:	Plate Rolls
Brand:	Metalmaster
Capacity:	2550 x 2.5mm
Speed Range (rpm):	~
Motor Power (kW / hp):	2.2 / 3
Voltage / Amperage (V / amp):	415

METALMASTER



Features

- Initial pinch rolls with pre-bending
- Motorised up & down rear curving roll enables quick & easy pre-bending
- Digital readout display on rear curving roll position
- Mobile foot pedal control with digital readout display
- Two rolls are powered by reduction gearbox drive system
- Swing out top roller enables cone or cylinder to be removed
- Safety wire interlock system with emergency shut-off
- Rolls include wiring grooves
- Includes a conical bending guide roller
- Mild steel capacity is rated on hot rolled material with 250MPA
- ORDER CODE: ZS806
- MODEL: PR-252A
- Curving System Type: Initial Pinch
- Curving Material Length: 2550mm
- Curving Plate Thickness - Mild Steel: 2.5mm
- Minimum Rolling Diameter: 225mm
- Roll Diameter: 150mm
- Motor Power: 2.2kW / 3hp
- Voltage / Amperage: 415V
- Dimensions (LxWxH): 3080 x 740 x 1200mm
- Shipping Dimensions (L x W x H): 308 x 74 x 120cm
- Nett Weight: 1875kg